



NOTES:

1. FOR USE WITH BOEING BMS13-65 OK & ADAMS RUSSELL FC48Z CABLES.
2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
3. FOR CRIMPING USE DIE KTH-2229.
4. INTERFACE PER MIL-STD-348, FIG. 304-1.
5. CENTER CONTACT (1-7273-1MA9) AND CRIMP SLEEVE (2-1664-1 M27) SUPPLIED UNASSEMBLED.
6. MARK PACKAGE: KINGS 1206-30-9 YRWK (DATE CODE)
7. MATERIALS:
 INSULATORS: TEFLON, ASTM-D-1710
 GASKET: SIL. RUB., A-A-59588
 K-GRIP SLEEVE: COM. BRONZE, ALLOY ASTM B135
 OUTER CONTACT, C-RING: PHOS. BRONZE, ASTM-B-103
 CRIMP CONTACT: BER. COP., ASTM-B-196
 ALL OTHER PARTS: BRASS, ASTM-B16
8. FINISHES:
 CONTACTS: .000050 MIN GOLD PLATE, PER ASTM-B-488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290 (RoHS)
 OUTER CONTACT: .000200 MIN SILVER PER ASTM-B-700 OVER .000020 MIN COPPER PER ASTM B734 (RoHS)
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
9. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 VOLTAGE RATING: 1000 VRMS
 FREQUENCY RANGE: DC TO 11 GHz
10. WEIGHT: 81.4 GRAMS

Ø .04
 Ø .02
 (3 HOLES)

MARK: KINGS 1206-30-9
 YRWK (DATE CODE)

1206-30-9	REVISIONS	
	ISSUE	CHANGES
	0	ER 35534 KH 04/15/94
	1	CN 35776 E KH 02/24/95
	2	CN 38323 E TML 06/18/01
E	CN 39510 C DRK 06/28/06	
	REVISED PER DMF304 & ER34270 CY 09/02/11	
CUSTOMER SALES DRAWING		
THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.		
SCALE 4:1		
APPROX SURFACE AREA		
WAS: E-18299		
CAGE CODE: 91836		
REF: BOEING		
PLUG, ANGLE, N		
DRAWN KH	DATE 04/08/94	
DESIGN JT	DATE 04/11/94	
APPR.	DATE	
 Winchester Electronics 42 Barnes Industrial Road, North Hellingford, CT 06482	B SIZE	
1206-30-9		