



NOTES:

1. FOR USE WITH BOEING BMS13-65 OF & ADAMS RUSSELL FC14Z CABLES.
2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
3. FOR CRIMPING USE DIE KTH-2211.
4. INTERFACE PER MIL-STD-348, FIG. 304-2.
5. CENTER CONTACT (1-534-89MA9) SUPPLIED UNASSEMBLED.
6. MARK PACKAGE: KINGS 1203-14-9 (DATE CODE)
7. MATERIALS:
 INSULATOR: TEFLON, ASTM D1710
 K-GRIP SLEEVE: COM. BRONZE TUBE, ASTM B135
 CENTER CONTACT: BER. COP., ASTM B196
 ALL OTHER PARTS: BRASS, ASTM B16
8. FINISHES:
 CENTER CONTACT: .000050 MIN. GOLD PLATE, PER ASTM B488 OVER .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
 ALL OTHER METAL PARTS: .000050 MIN. NICKEL PER AMS-QQ-N-290 OVER .000050 MIN. COPPER PER ASTM B734 (RoHS)
9. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 VOLTAGE RATING: 1000 VRMS
 FREQUENCY RANGE: DC TO 11 GHz
10. WEIGHT: 33.0 GRAMS

1203-14-9

REVISIONS	
ISSUE	CHANGES
0	ER 33876 JCA 04/14/92
1	CN 37437 A VLS 09/10/98
C	REVISED PER DMF304 & ER34488 KPL 08/16/11

CUSTOMER
SALES
DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

WAS: E-17410

CAGE CODE: 91836

REF: BOEING

JACK, N

DRAWN JCA DATE 04/14/92

DESIGN JT DATE 04/15/92

APPR. DATE

WINCHESTER Winchester Electronics Corporation
62 Barnes Industrial Road North
ELECTRONICS Wallingford, Connecticut 06492

1203-14-9