

## FEATURES

- ◆ RoHS compliant
- ◆ Efficiency up to 83%
- ◆ SIP Package
- ◆ Wide temperature performance at full 2 Watt load, -40°C to 85°C
- ◆ UL 94V-0 package material
- ◆ No heatsink required
- ◆ Low ripple and good EMC Features
- ◆ Industry standard pinout
- ◆ Power sharing on output
- ◆ 3KVDC isolation
- ◆ Continuous Short Circuit Protection
- ◆ Internal SMD construction
- ◆ No external components required
- ◆ Good dynamic feature

## MODEL SELECTION

### IE<sup>①</sup>05<sup>②</sup>05<sup>③</sup>X<sup>④</sup>S<sup>⑤</sup>-2W<sup>⑥</sup>

- ① Product Series
- ② Input Voltage
- ③ Output Voltage
- ④ Fixed Input
- ⑤ SIP Package
- ⑥ Rated Power

## APPLICATIONS

The IE\_XS-2W series are specially designed for applications where a group of polar power supplies are isolated from the input power supply in a distributed power supply system on a circuit board.

These products apply to:

- 1) where the voltage of the input power supply is fixed (voltage variation  $\leq \pm 5\%$ );
- 2) where isolation is necessary between input and output (isolation voltage  $\leq 3000\text{VDC}$ );
- 3) where the regulation of the output voltage and the output ripple noise are demanded.



# CE REACH

MICRODC reserves the copyright

## SELECTION GUIDE

Order code	Input		Output			Efficiency (% Typ)	Switching Frequency (KHz Typ)
	Voltage (VDC)		Voltage (VDC)	Current (mA)			
	Nominal	Range		Max	Min		
IE0505XS-2W	5	4.75-5.25	$\pm 5$	$\pm 100$	$\pm 10$	70	85
IE0509XS-2W	5	4.75-5.25	$\pm 9$	$\pm 56$	$\pm 6$	61	83
IE0512XS-2W	5	4.75-5.25	$\pm 12$	$\pm 42$	$\pm 5$	62	83
IE0515XS-2W	5	4.75-5.25	$\pm 15$	$\pm 33$	$\pm 4$	64	250
IE1205XS-2W	12	11.4-12.6	$\pm 5$	$\pm 100$	$\pm 10$	75	120
IE1209XS-2W	12	11.4-12.6	$\pm 9$	$\pm 56$	$\pm 6$	61	83
IE1212XS-2W	12	11.4-12.6	$\pm 12$	$\pm 42$	$\pm 5$	65	83
IE1215XS-2W	12	11.4-12.6	$\pm 15$	$\pm 33$	$\pm 4$	64	83
IE2405XS-2W	24	22.8-25.2	$\pm 5$	$\pm 100$	$\pm 10$	78	83
IE2409XS-2W	24	22.8-25.2	$\pm 9$	$\pm 56$	$\pm 6$	69	83
IE2412XS-2W	24	22.8-25.2	$\pm 12$	$\pm 42$	$\pm 5$	63	83
IE2415XS-2W	24	22.8-25.2	$\pm 15$	$\pm 33$	$\pm 4$	74	300

## ISOLATION SPECIFICATIONS

Parameter	Test conditions	Min.	Typ.	Max.	Units
Isolation test voltage	Flash tested for 1 minute and 1mA max	3000			VDC
Isolation resistance	Test at Viso=500VDC	1000			MΩ

## OUTPUT SPECIFICATIONS

Parameter	Test conditions	Min	Typ.	Max.	Units
Output power		0.2		2	W
Line regulation	For Vin change of $\pm 5\%$			$\pm 0.5$	%
Load regulation	10% to 100% full load			$\pm 1.5$	%
Output voltage accuracy	100% full load			$\pm 3$	%
Temperature drift	100% full load			0.03	%/°C
Output Ripple*	20MHz Bandwidth		20	30	MV p-p
Output Noise*	20MHz Bandwidth		50	150	MV p-p
Switching frequency	Full load, nominal input		100		Khz

\* Test ripple and noise by "parallel cable" method. See detailed operation instructions at Testing of Power Converter section, application notes.


### TEMPERATURE CHARACTERISTICS

Parameter	Conditions	Min.	Typ.	Max.	Units
Storage humidity range				95	%
Operating temperature		-40		85	°C
Storage temperature		-55		125	°C
Lead temperature	1.5mm from case for 10 seconds		40	58	°C
Temp.rise at full load				300	°C
Cooling		Free air convection			
Case material		Plastic(UL94-V0)			
Short circuit protection	IE-XS-2W	Continuous			
MTBF		3500			K hours
Weight			5.2		g

\*Supply voltage must be discontinued at the end of short circuit duration.


### TYPICAL CHARACTERISTICS

Temperature Derating Graph




### OUTLINE DIMENSIONS & PIN CONNECTIONS

SIZE Graph



RECOMMENDED FOOTPRINT  
Top view, grid: 2.54mm(0.1inch)  
diameter: 1.00mm(0.039inch)



#### FOOTPRINT DETAILS

Pin	Function
1	VIN
2	GND
7	+Vo
9	-Vo
10	0V

Note:  
Unit:mm(inch)  
Pin section:0.50\*0.3mm(0.020\*0.012inch)  
Pin section tolerances:±0.10mm(±0.004inch)  
General tolerances:±0.25mm(±0.010inch)


All specifications typical at TA=25°C, nominal input voltage and rated output current unless otherwise specified. Another 24V products, please inquire Our technical department!

#### Requirement on output load

To ensure this module can operate efficiently and reliably, a minimum load is specified for this kind of DC/DC converter in addition to a maximum load(namely full load).During operation, make sure the specified range of input voltage is not exceeded,the minimum output load is **not less than 10%** of the full load, and that this product should never be operated under no load!

### Filtering

To get an extreme low ripple,an "LC"filtering network may be connected to the input and output ends of the DC/DC converter.Which may produce a more significant filtering effect.It should also be noted that the inductance and the frequency of the "LC"filtering network should be staggered with the DC/DC frequency to avoid mutual interference see (Figure 1).



(Figure 1)

In some circuits which are sensitive to noise and ripple.a filtering capacitor may be added to the DC/DC output end and input end to reduce the noise and ripple. However, the capacitance of the output filter capacitor must be proper. If the capacitance is too big, a startup problem might arise. For every channel of output, provided the safe and reliable operation is ensured, the greatest capacitance of its filter capacitor sees (Table 1).

EXTERNAL CAPACITOR TABLE (TABLE 1)

Vin (VDC)	Cin (μF)	Vout (VDC)	Cout (μF)
5	4.7	±5	4.7
12	2.2	±9	2.2
24	0.47	±12	1.0

It's not recommend to connect any external capacitor in the application field with less than 0.5 watt output.

### Overload Protection

Under normal operating conditions , the output circuit of these products has no protection against over-current and short-circuits.The simplest method is to connect a self-recovery fuse in series at the input end or add a circuit breaker to the circuit.

**When the environment temperature is higher than 71° C, the product output power should be less than 60% of the rated power.**

**No parallel connection or plug and play.**

**Use dual output simultaneously, forbid opening Output pin (0V) to use as single output.**

#### RoHS COMPLIANT INFORMATION

This series is compatible with RoHS soldering systems with a peak wave solder temperature of 300° C for 10 seconds.  
The pin termination finish on the SIP package type is Tin Plate, Hot Dipped over Matte Tin with Nickel Preplate. The DIP types are Matte Tin over Nickel Preplate. Both types in this series are backward compatible with Sn/Pb soldering systems.

#### REACH COMPLIANT INFORMATION

This series has proven that this product does not contain harmful chemicals, it also has harmful chemical substances through the registration, inspection and approval.