

Part Number: C1206

Revision Level: 4

Date: 11/20/2007

**6C 18 AWG 41/34 TC RUBBER OAS CAROLPRENE\***

**CONTROL CABLE**

**A. CONSTRUCTION**

**DIAMETERS**

Conductor:	#18 AWG 41/34 Tinned Copper	0.049" nom.
Insulation:	0.020" Wall Rubber	0.091" nom.
Cable:	6 conductors @ 3.00" LHL with jute filler & overall mylar wrap.	0.270" nom.
Braid	#36 AWG Tinned Copper 80% Min. Coverage	0.290" nom.
Tape:	Cotton Separator	0.300" nom.
Jacket:	0.035" Wall Carolprene* - Black	0.370" +/- 0.019"
Print Legend:	<b>CAROL C-1206A VW-1 MADE IN USA</b>	

**B. INDUSTRY APPROVALS**

NONE

**C. ELECTRICAL PROPERTIES**

TEMPERATURE:	60 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	7.1 Ohms/1000 ft nom

**D. COLOR CODE** *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	White
3	Red
4	Green
5	Blue
6	Brown