AX6033

4-slot ShoeBox Chassis





▲ Front view ▲ Interior view

Features

Desktop or wallmount industrial computer chassis

*Specifications and certifications are based on options and may vary.

With ATX6020/4, AT 70W power supply

With ATX6021/4, AT 70W power supply

Without BP, with AT 100W power supply

Slots per Segment

(ISA/PCI/PCIe/CPU)

4/0/0

0/3/1

Segment

Single

Single

• One 5.25" and two 3.5" HDD drive bays

Ordering Information

Backplane Options

Models

ATX6020/4

ATX6021/4

AX6033WI/70

AX6033WC/70

AX6033WB/100

PICMG 1.0

• Equipped with a PS/2 type power supply

Overview

Embedded

Embedded Systems for Transportation

Embedded Field Controllers

Embedded MicroBoxes

Industrial

Barebone Systems Industrial

Chassis

Backplanes

Power Supplies

Peripherals & Accessories

Appendix


Specifications

Standard Color	Beige (PANTONE 414C)	
Construction	Heavy-duty steel	
Drive Capacity	Exposed 1 x 3.5" HDD drive bay and one slim CD-ROM drive Internal 1 x 3.5" HDD drive bay	
Cooling	1 x 8 cm ball-bearing fan (42.5 CFM/each) with a removable filter	
Front Panel Indicators	1 x power on/off; 1 x HDD	
Rear Panel Controls	1 x power on/off; 1 x system reset	
Pre-punched Rear Panel	2 x 9-pin; 1 x 25-pin; 2 x USB	
System Board	Half-size SBCs	
Expansion Interface	4-slot ISA or PCI backplane	
Operating Temperature Range	0°C ~ 45°C (32°F ~ 113°F)	
Dimensions	160 mm (6.3") (W) x 275 mm (10.8") (D) x 185 mm (7.3") (H)	
Weight (net/gross)	4.5 kg (9.92 lb)/5.7 kg (12.57 lb)	

Power Supply Specifications

Items	Input	Specifications Output	MTBF
AC AT 70W	AC 115/230V (Auto)	+5V @ 10A +12V @ 1.5A -12V @ 0.3A	100,000 hours
DC AT 72W	DC 36~72Vpc	+5V @ 10A +12V @ 1.5A -12V @ 0.3A	100,000 hours
AC AT 100W	DC 115/230Vpc (Auto)	+5V @ 15A +12V @ 12A -12V @ 0.5A	100,000 hours

Dimensions



^{*} All specifications and photos are subject to change without notice. © 2013 Axiomtek Co., Ltd. All rights reserved.