

Part Number: C0452A

Revision Level: 4

Date: 8/2/2007

2C 20 7/28 TC PVC OAS PVC

COMMUNICATION CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#20 AWG 7/28 Tinned Copper	0.038" nom.
Insulation:	0.013" Wall Polyvinyl Chloride	0.064" nom.
Cable:	2 conductors @ 2.00" LHL with alum./polyester (foil out) & #22 AWG 7/30 TC drain wire.	0.133" nom.
Jacket:	0.037" Wall Polyvinyl Chloride	0.207" +/- 0.01"
Print Legend:	CAROL (R) 20 AWG -- C0452A -- 105C TYPE PLTC 300V E60233-8 (UL) -- MADE IN USA (DATE CODE)	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type PLTC

C. ELECTRICAL PROPERTIES

TEMPERATURE:	105 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	10.3 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	50 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	89.5 pF/ft @ 1kHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red