



# Frontier Electronics Corp.

667 E. COCHRAN STREET, SIMI VALLEY, CA 93065

TEL: (805) 522-9998 FAX: (805) 522-9989




E-mail: [frontiersales@frontierusa.com](mailto:frontiersales@frontierusa.com)

Web: <http://www.frontierusa.com>

## 16A SCHOTTKY BARRIER RECTIFIERS

### SRF16-03 THRU SRF16-10

CASE : ITO-220AC( SRF16-XX ) , FULLY INSULATED PACKAGE



	MILLIMETERS	
	MIN	MAX
B	9.72	10.27
C	6.30	6.90
D	14.50	15.50
E	13.00	13.80
F	-	4.1
G	4.95	5.20
H	-	1.52
I	-	0.9
J	-	4.8
K	-	3.1
L	2.5	2.9
M	-	0.8
O	-	Ø 3.4

#### FEATURES

- EXTREMELY LOW VF
- LOW STORED CHARGE, MAJORITY CARRIER CONDUCTION
- LOW POWER LOSS / HIGH EFFICIENCY
- UL 94V0 FLAME RETARDANT EPOXY MOLDING COMPOUND

#### MECHANICAL DATA

- CASE: TRANSFER MOLDED
- LEADS: SOLDERABLE PER MIL-STD-202,METHOD 208
- POLARITY: AS MARKED
- WEIGHT 1.81 GRAMS

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS RATINGS AT 25°C AMBIENT TEMPERATURE UNLESS OTHERWISE SPECIFIED SINGLE PHASE, HALF WAVE, 60 HZ, RESISTIVE OR INDUCTIVE LOAD. FOR CAPACITIVE LOAD, DERATE CURRENT BY 20%

RATINGS	SYMBOL	SRF16	SRF16	SRF16	SRF16	SRF16	SRF16	SRF16	SRF16	SRF16	UNITS
		-03	-035	-04	-045	-05	-06	-08	-09	-10	
MAXIMUM RECURRENT PEAK REVERSE VOLTAGE	$V_{RRM}$	30	35	40	45	50	60	80	90	100	V
MAXIMUM RMS VOLTAGE	$V_{RMS}$	21	24	28	31	35	42	56	63	70	V
MAXIMUM DC BLOCKING VOLTAGE	$V_{DC}$	30	35	40	45	50	60	80	90	100	V
MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT SEE FIG.1	$I_O$	16.0									A
PEAK FORWARD SURGE CURRENT, 8.3ms SINGLE HALF SINE-WAVE SUPERIMPOSED ON RATED LOAD	$I_{FSM}$	200									A
STORAGE TEMPERATURE RANGE	$T_{STG}$	- 55 TO + 150									°C
OPERATING TEMPERATURE RANGE	$T_{OP}$	- 55 TO + 125									°C

#### ELECTRICAL CHARACTERISTICS ( $A_T T_A = 25^\circ C$ UNLESS OTHERWISE NOTED)

CHARACTERISTICS	SYMBOL	SRF16	SRF16	SRF16	SRF16	SRF16	SRF16	SRF16	SRF16	SRF16	UNITS
		-03	-035	-04	-045	-05	-06	-08	-09	-10	
MAXIMUM FORWARD VOLTAGE AT $I_O$ PER LEG	$V_F$	0.60			0.70		0.85				V
MAXIMUM REVERSE CURRENT AT 25°C PER LEG (NOTE 1)	$I_R$	5.0									mA
MAXIMUM REVERSE CURRENT AT 100°C PER LEG (NOTE 1)	$I_R$	50.0									mA

#### THERMAL CHARACTERISTICS ( $T_C = 25^\circ C$ UNLESS OTHERWISE NOTED)

PARAMETER	SYMBOL	SRF16	UNITS
TYPICAL THERMAL RESISTANCE JUNCTION TO CASE PER LEG	$R_{\theta jc}$	5.0	°C/W

NOTES: 1. PULSE TEST: 300µS PULSE WIDTH, 1% DUTY CYCLE

# RATINGS AND CHARACTERISTIC CURVES SRF16-03 THRU SRF16-10

FIG. 1 - FORWARD DERATING CURVE




FIG. 2 - PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS




FIG. 4 - TYPICAL FORWARD CHARACTERISTIC

