


MANO830

Intel® Atom™ D2550 Mini ITX SBC with Intel® NM10 Chipset, VGA/HDMI/LVDS, PCI Express Mini Card, PCIe x1 and HD Audio

NEW



Fanless

Low Power

DualView

DDR3

PCIe Mini

+12V

System

CPU	Intel® Atom™ Cedarview D2550 processor
System Memory	1 x 204-pin SO-DIMM dual channel DDR3-1066 max. up to 4 GB
Chipset	Intel® NM10
BIOS	AMI
SSD	N/A
Watchdog Timer	Reset: 1-65535 level
Expansion Interface	1 x PCIe x1 1 x PCI Express Mini Card
Battery	Lithium 3V/220 mAH
Power Requirements	TBD
Size	170 x 170 mm
Board Thickness	1.6 mm
Temperature	0° ~ +60°C (32°F ~ 140°F), operation
Operation Humidity	10% ~ 95% relative humidity, non-condensing

I/O


MIO	1 x PS/2 keyboard and mouse 6 x RS-232 (COM 1 ~ 6) 1 x LPT 1 x RJ-11
SATA	2 SATA-300
Ethernet	1 x Realtek RTL8111E for Gigabit LAN
Audio	HD Audio as Mic-in/Line-out with Realtek ALC892
USB	7 x USB 2.0
TPM	N/A
Digital I/O	8 Channels (4-IN & 4-OUT)
SM BUS	N/A

Display

Display Chipset	Intel® GMA graphic core
Memory Size	Shared Memory
Display Interface	1 x VGA 1 x HDMI 1 x LVDS 24bit single channel

Features

- Intel® Atom™ Cedarview D2550 processor
- 1 DDR3-1066 MHz max. up to 4 GB
- PCIe x1 support
- 7 USB 2.0 supported
- 2 SATA-300 supported
- PCI Express Mini Card supported
- DC-IN 12V supported
- Dual view display



▲ Side view

Packing List

User's manual/utility CD, cable, I/O bracket

Ordering Information

Standard

MANO830	Mini ITX SBC with Intel® Atom™ D2550, VGA/HDMI/LVDS, PCI Express Mini Card, PCIe x1, 1 10/100/1000Mbps Ethernet, 6 COM, 7 USB and HD Audio
---------	--

SBC
Services
and Solutions

Systems
on
Modules

Embedded
SBCs
>EPIC

Embedded
SBCs
>3.5" Capa

Embedded
SBCs
>Nano-ITX

Embedded
SBCs
>Pico-ITX

Embedded
SBCs
>PC/104

Industrial
Mother-
boards

Slot
CPU
Cards

Accessories

Appendix