



# RS1AB-RS1MB

Surface Mount Rectifiers

**REVERSE VOLTAGE: 50 -- 1000 V**  
**CURRENT: 1.0A**


## Features

- ◇ Plastic package has underwriters laborator flammability classification 94V-0
- ◇ For surface mounted applications
- ◇ Low profile package
- ◇ Built-in strain relief,ideal for automated placement
- ◇ Glass passivated chip junction
- ◇ High temperature soldering:  
250°C/10 seconds at terminals

## Mechanical Data

- ◇ Case:JEDEC DO-214AA,molded plastic over passivated chip
- ◇ Polarity: color band denotes cathode end
- ◇ Weight: 0.003 ounces, 0.093 gram

### DO - 214AA(SMB)



Dimensions in millimeters

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

		RS1AB	RS1BB	RS1DB	RS1GB	RS1JB	RS1KB	RS1MB	UNITS
Maximum recurrent peak reverse voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V <sub>RWS</sub>	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	V
Maximum average forward rectified current @ T <sub>A</sub> =90°C	I <sub>F(AV)</sub>					1.0			A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I <sub>FSM</sub>				30.0				A
Maximum instantaneous forward voltage at 1.0A	V <sub>F</sub>				1.30				V
Maximum DC reverse current @T <sub>A</sub> =25°C at rated DC blocking voltage @T <sub>A</sub> =125°C	I <sub>R</sub>				5.0				µA
					50.0				
Maximum reverse recovery time (NOTE 1)	t <sub>rr</sub>		150		250	500			ns
Typical junction capacitance (NOTE 2)	C <sub>J</sub>			10		7.0			pF
Typical thermal resistance (NOTE 3)	R <sub>θJA</sub> R <sub>θJL</sub>			105 32					°C/W
Operating junction and storage temperature range	T <sub>J</sub> T <sub>STG</sub>			- 55 ----- + 150					°C


NOTE: 1.Reverse recovery time test conditions:I<sub>F</sub>=0.5A,I<sub>R</sub>=1.0A,I<sub>rr</sub>=0.25A

2. Measured at 1.0MHz and applied reverse voltage of 4.0 Volts


3. Thermal resistance from junction to ambient and junction to lead P.C.B.mounted on 0.2"X0.2"(5.0X5.0mm<sup>2</sup>) copper pad areas

## Ratings AND Characteristic Curves


**Fig. 1 — Forward Current Derating Curve**




**Fig. 2 — Maximum Non-Repetitive Peak Forward Surge Current**




**Fig. 3 — Typical Instantaneous Forward Characteristics**



**Fig. 4 — Typical Reverse Characteristics**



**Fig. 5 — Typical Junction Capacitance**



**Fig. 6 — Typical Transient Thermal Impedance**

