High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#: ATS-55330D-C1-R0

Description: High Performance X-CUT - Heat Sink, T412, BLACK-ANODIZED

Heat Sink Type: Cross-Cut

Heat Sink Attachment: THERMAL TAPE
Equivalent Part Number: ATS-55330D-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- · High efficiency cross-cut fin design provides low pressure drop characteristics
- · Large surface area increases heat sink performance
- Designed specifically for BGAs and other surface mount packages
- · Comes pre-assembled with high performance thermal interface material

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	12.30 °C/W	8.74 °C/W	7.56 °C/W	6.79 °C/W	6.22 °C/W	5.79 °C/W	5.43 °C/W
	Ducted Flow	n/a						

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
	33.0 mm	33.0 mm	9.5 mm	mm	T412	BLACK-ANODIZED
*Image above is for illustration purpose only.	Dimension ATS-5533 (Saint Go Thermal papplication ATS reserperforman ATS certification	30D-C2-R0 is the exbain C675). performance data arin. rives the right to updice.	neight from the botto act heat sink assem e provided for refere ate or change its pro-	ence only. Actual pe oducts without notic S-6 and REACH cor	ent thermance to impr	al interface material e may vary by



