



[PAGE BACK](#) [CLOSE](#)

**Product Name**    **3-terminal Filters**  
**Series**            **ACF Series**  
**Type**              **321825 Type**  
**Part Number**    **ACF321825-151-TD01**

Product Lifecycle Stage    PROD



#### Specification

Mounting Method Flag	Yes	
Processing	MULTI-LAYER	
Shape	Chip	
Circuit Type	T Type	
Number of Circuits	Nom	1
Size Code	3218	
Body Length(L)	Nom	3.2 m m
Body Breadth(W)	Nom	1.8 m m
Body Height(T)	Nom	2.5 m m
Rated Capacitance	Nom	150 p F
Rated Voltage	Max	20 V
Rated Current	Max	300 m A
Insulation Resistance	Min	1000 M Ohm
DC Resistance	Max	0.15 Ohm
Attenuation	Min	25 dB
Frequency Range of Attenuation	Min	205 M Hz
	Max	280 M Hz
Polarity Marking	No	
Soldering Method	Reflow,Iron Soldering	
Category Temperature	Min	-25 Cel
Range	Max	85 Cel
Storage Temperature Range	Min	-40 Cel
	Max	85 Cel
Weight	Nom	0.07 g

#### Summary/Applications/Feature

Summary	The ACF Series are T-type EMC filters incorporating ferrite chip beads and multilayer ceramic chip capacitors.	
Applications	EMC filters for signal line and interface	
Feature	The ACF Series are T-type EMC filters incorporating ferrite chip beads and multilayer ceramic chip capacitors.	

#### Packaging

Packing	Blister (Plastic)Taping [180mm Reel]	
Minumum Package Qty	Nom	1000 Pcs
Minimum Order Qty	Nom	1000 Pcs

[Details](#)

#### ☛ [ Caution ]

Specifications which provide more details for the proper and safe use of the described product are available upon request.

#### ☛ [ Notice of Revision and Improve ]

All specifications are subject to change without notice.

[PAGE TOP](#)

Copyright(c) 1996-2008 All rights reserved.