

CONTACT TYPES and TERMINATION Styles available

	ELECTRICAL RATING	50 Ω		SOLDER		PCB MOUNT	PRESS-FIT
1.1	1A	_	_	1	-	/	1
	_	1	1	1	1	✓	-
	10A-40A	_	_	1	1	1	1
	2.8 KV, 1.5 Amps	-	-	1			_
in the	Multimode	(50-1	00 Mic	ron Core	Diamete	er)	

Litten

HYBRID DIN MULTIPURPOSE CONNECTORS

Winchester Hybrid Din Multipurpose Connectors are offered with a wide array of insulator and contact configurations. In addition to standard solder tails, selected contacts are also available with the Winchester C-Press* compliant pin termination...THE MOST RELIABLE PRESS-FIT CONTACT AVAILABLE.

AVAILABLE CONNECTOR CONFIGURATIONS

STYLE	TAIL CONFIGURATION			
per DIN 41612	Straight Solder	Right Angle Solder	Straight C-Press®	
M Female	6063 Series		6163 Series (uses flat-rock tooling)	
M Male		6063 Series		
Inverse M Female		6093 Series		
Inverse M Male	6093 Series		6093 Series 6105 Series	

AVAILABLE INSULATOR STYLES	No. of Signal Positions	No. of Contact Positions
	78	2
	60	4
	42	6
	24	8
	6	10

For more information about Hybrid Din Multipurpose Connectors contact our customer service department.

Litton

C-Press is a registered trademan, of Latter Systems, Inc.

1.05