


Central
Semiconductor Corp.
Central
Semiconductor Corp.
Central
Semiconductor Corp.
CentralTM
Semiconductor Corp.

145 Adams Avenue
Hauppauge, New York 11788



1N5550
1N5551
1N5552
1N5553
1N5554

GLASS PASSIVATED RECTIFIER
3.0 AMPS, 200 THRU 1000 VOLTS

GPR-3A CASE

DESCRIPTION


The CENTRAL SEMICONDUCTOR 1N5550 series types are silicon rectifiers mounted in a hermetically sealed, glass passivated package for general applications where high reliability is desired.

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

	SYMBOL	1N5550	1N5551	1N5552	1N5553	1N5554	UNIT
Peak Repetitive Reverse Voltage	V_{RRM}	200	400	600	800	1000	V
DC Blocking Voltage	V_R	200	400	600	800	1000	V
RMS Reverse Voltage	$V_R(\text{RMS})$	140	280	420	560	700	V
Average Forward Current ($T_A=55^{\circ}\text{C}$)	I_O			3.0			A
Peak Forward Surge Current	I_{FSM}			150			A
Operating and Storage Junction Temperature	T_J, T_{STG}			-65 TO +200			$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
I_R	$V_R=\text{Rated } V_{RRM}$		1.0	μA
I_R	$V_R=\text{Rated } V_{RRM}, T_A=100^{\circ}\text{C}$		75	μA
V_F	$I_F=3.0\text{A}$ (200V thru 600V)		1.0	V
V_F	$I_F=3.0\text{A}$ (800V thru 1000V)		1.1	V
BVR	$I_R=50\mu\text{A}$ (1N5550)	240		V
BVR	$I_R=50\mu\text{A}$ (1N5551)	460		V
BVR	$I_R=50\mu\text{A}$ (1N5552)	660		V
BVR	$I_R=50\mu\text{A}$ (1N5553)	880		V
BVR	$I_R=50\mu\text{A}$ (1N5554)	1100		V
t_{rr}	$I_F=0.5\text{A}, I_R=1.0\text{A}, \text{Recov. to } 0.25\text{A}$ (200V thru 600V)		2.0	μs
t_{rr}	$I_F=0.5\text{A}, I_R=1.0\text{A}, \text{Recov. to } 0.25\text{A}$ (800V thru 1000V)		4.0	μs



DIMENSIONS IN INCHES (MILLIMETERS)

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824