

JMACG-26XPS Product Details



Military/Aerospace High Performance Relays
[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- MA TO-5 Relay Series
- Input Voltage = 26.5 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 1 Amps.
- Non Polarized, Monostable Coil Magnetic System

[View all Features](#)

Quick Links
[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

JMACG-26XPS
(3-1617122-4)
TE Internal Number: 3-1617122-4
 [Active](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information	
Product Drawings: - None Available Catalog Pages/Data Sheets: RELAY (PDF, English) Product Specifications: - None Available Application Specifications: - None Available Instruction Sheets: - None Available CAD Files: - None Available	Additional Information: Product Line Information Related Products: Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Termination Type = Long Leads Electrical Characteristics: - Input Voltage (VDC) = 26.5 - Contact Current Rating (Amps.) = 1 - Coil Polarity Protection Diode = Without - Transistor Driver = Without - Coil Resistance (?) = 1560 - MOSFET Driver = Without - Coil Power Measurement = Milliwatts - Coil Power, Nominal (mW) = 450 - Actuating System = DC - Shock = 75 G's, 6ms - Vibration = 30G's, 10 to 3000Hz Body Related Features: Series = MA TO-5 Relay Contact Related Features: - Mounting Options = PC Board - Enclosure = Hermetically Sealed - Approved Standards = M39016 Qualified, P Level - Pin Configuration = .200" x .300" Spreader Pad	Configuration Related Features: Contact Arrangement = 2 Form C, DPDT, 2 C/O - Coil Magnetic System = Non Polarized, Monostable - Coil Suppression Diode = Without Industry Standards: - Government/Industry Qualification = Yes - Government/Industry Part Number = M39016/9-104P RoHS/ELV Compliance = Not ELV/RoHS compliant Lead Free Solder Processes = Not suitable for lead free processing Conditions for Usage: - Temperature Range (?C) = -65 - +125 Other: - Brand = CII

Corporate Information

[Who We Are](#)

[Investors](#)

[News Room](#)

[Supplier Portal](#)

[Careers](#)

Quick Links

[Check Distributor Inventory](#)

[Cross Reference](#)

[Find Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

Customer Support

[Email or Chat with Us](#)

[Find a Phone Number](#)

[Search Knowledge Base](#)

[Manage Your Account](#)