

Component to wire connectors SICMA

3 way aggregate housings for 1.5 mm terminals

Features

- Reduced size sealed housings
- Circumferential interface seal
- Rear sealing ensured by a pre-mounted grommet
- Pre-assembled front grids support blade terminal guiding and mating
- Terminal position assurance (T.P.A.)
- Several colour codings available



Part Numbers	No. of position	Terminal size	Type	Colour
210 PC032S9004	3	1.5 mm	Female housing	White
210 PC032S0004	3	1.5 mm	Female housing	Black
210 PC032S8004	3	1.5 mm	Female housing	Grey
210 PC032S6004	3	1.5 mm	Female housing	Blue
210 A037005	3	1.5 mm	Filler plug	Violet

Performance characteristics

- Temperature range :
from -40°C to +125°C
- Contact retention force : > 65 N
- Contact insertion force : < 15 N
- Sealing protection : IP 68
- Acceptable wire range :
from 0.6 to 2 mm²

Construction

- Housing material : PBT
- Interfacial seal : Silicone
- Rear grommet seal : Silicone

Tooling

- T.P.A. removal tool : 210S040
- Terminal removal tool : 210S041

Connector compatibility

- Usable terminals :
 - Sicma-1 1.5 mm female terminals
 - Sicma-2 1.5 mm female terminals
 - Sicma-3 1.5 mm female terminals

Component to wire connectors SICMA

Dimensional characteristics

