



Gull Wing PICO PART NUMBER	J Lead PICO PART NUMBER	PRIMARY IMPEDANCE OHMS	SECONDARY IMPEDANCE OHMS SPLIT WINDINGS		POWER MILLIWATTS 400 HZ and higher		PRIMARY UNBAL DC CURRENT ma	PRIMARY DC resistance OHMS	SECONDARY DC RESISTANCE OHMS		TURNS/RATIO PRIM/SEC		PICO PRICES 1-9***
			SER	PAR	1KHz and higher	1KHz and higher			SER COVN	PAR COVN	SER COVN	PAR COVN	
71350	81350	3000 ct	3000 ct	725	.4	.075	1.8	300	360	90	1:1	2:1	27.28
71355	81355	*3000 ct	3000 ct	-	.4	.075	1.8	300	360	-	1:1	-	37.13
71360	81360	3600 ct	3600 ct	900	.4	.075	1.7	360	432	108	1:1	2:1	27.28
71365	81365	4000 ct	16ct	4	.4	.075	1.6	400	1.9	.47	15.8:1	31.8:1	33.53
71370	81370	4000 ct	600 ct	150	.4	.075	1.6	400	72	18	2.58:1	5.16:1	33.53
71375	81375	4000 ct	1000 ct	250	.4	.075	1.6	400	120	30	2:1	4:1	37.13
71380	81380	*4000 ct	8000 ct	-	.4	.075	1.6	400	960	-	1:1.41	-	37.13
71385	81385	5000 ct	500 ct	125	.4	.075	1.4	500	60	15	3.16:1	6.32:1	28.42
71390	81390	5000 ct	5000 ct	1250	.4	.075	1.4	500	600	150	1:1	2:1	28.42
71395	81395	7500 ct	50 ct	12.5	.33	.075	1.2	750	6	1.5	12.2:1	24.5:1	28.42
71400	81400	7500 ct	100 ct	25	.33	.075	1.2	750	12	3	8.66:1	17.3:1	28.42
71405	81405	7500 ct	600 ct	150	.33	.075	1.2	750	72	18	3.54:1	7.07:1	31.63
71410	81410	7500 ct	2500 ct	625	.33	.075	1.2	750	300	75	1.73:1	3.46:1	31.63
71415	81415	*7500 ct	7500 ct	-	.33	.075	1.2	750	900	-	1:1	-	37.13
71420	81420	8000 ct	12.8 ct	3.2	.3	.075	1.1	800	1.5	.38	25:1	50:1	28.42
71425	81425	8000 ct	1000 ct	250	.3	.075	1.1	800	120	30	2.83:1	5.66:1	31.63
71430	81430	*8000 ct	1200 ct	-	.3	.075	1.1	800	144	-	2.58:1	-	37.13
71435	81435	*9000 ct	9000 ct	-	.27	.075	1.1	900	1080	-	1:1	-	37.13
71440	81440	10,000 ct	12.8 ct	3.2	.25	.075	1.0	1000	1.5	.38	28:1	56:1	25.69
71445	81445	10,000 ct	16 ct	4	.25	.075	1.0	1000	1.92	.48	25:1	50:1	25.69
71450	81450	10,000 ct	100 ct	25	.25	.075	1.0	1000	12	3	10:1	20:1	28.42
71455	81455	10,000 ct	200 ct	50	.25	.075	1.0	1000	24	6	7.07:1	14.14:1	28.42
71460	81460	10,000 ct	500 ct	125	.25	.075	1.0	1000	60	15	4.47:1	8.94:1	28.42
71465	81465	10,000 ct	600 ct	150	.25	.075	1.0	1000	72	18	4.08:1	8.16:1	28.42
71470	81470	10,000 ct	1000 ct	250	.25	.075	1.0	1000	120	30	3.16:1	6.32:1	28.42
71475	81475	10,000 ct	1200 ct	300	.25	.075	1.0	1000	144	36	2.89:1	5.77:1	33.53
71480	81480	10,000 ct	1500 ct	375	.25	.075	1.0	1000	180	45	2.58:1	5.16:1	33.53
71485	81485	10,000 ct	2000 ct	500	.25	.075	1.0	1000	240	60	2.24:1	4.47:1	32.86
71490	81490	10,000 ct	5000 ct	1250	.25	.075	1.0	1000	600	150	1.41:1	2.83:1	33.42
71495	81495	10,000 ct	7500 ct	1875	.25	.075	1.0	1000	900	225	1.15:1	2.3:1	33.53
71500	81500	10,000 ct	10,000 ct	2500	.25	.075	1.0	1000	1200	300	1:1	2:1	32.32
71505	81505	*10,000 ct	10,000 ct	-	.25	.075	1.0	1000	1200	-	1:1	-	37.13
71510	81510	15,000 ct	400 ct	100	.16	.075	.82	1500	48	12	6.12:1	12.24:1	32.32
71515	81515	15,000 ct	500 ct	125	.16	.075	.82	1500	60	15	5.48:1	10.95:1	32.32
71520	81520	15,000 ct	600 ct	150	.16	.075	.82	1500	72	18	5:1	10:1	32.32
71525	81525	15,000 ct	10,000 ct	2500	.16	.075	.82	1500	1200	300	1.22:1	2.45:1	32.32
71530	81530	*15,000 ct	15,000 ct	-	.16	.075	.82	1500	1800	-	1:1	-	37.13
71535	81535	15,000 ct	15,000 ct	3750	.16	.075	.82	1500	1800	450	1:1	2:1	33.53
71540	81540	18,000 ct	1000 ct	250	.15	.075	.80	1600	120	30	4:1	8:1	33.53
71545	81545	20,000 ct	500 ct	125	.125	.075	.70	2000	60	15	6.33:1	12.65:1	30.95
71550	81550	20,000 ct	600 ct	150	.125	.075	.70	2000	72	18	5.77:1	11.55:1	30.95
71555	81555	20,000 ct	800 ct	200	.125	.075	.70	2000	96	24	5:1	10:1	29.58
71560	81560	20,000 ct	1000 ct	250	.125	.075	.70	2000	120	30	4.47:1	8.94:1	37.13
71565	81565	20,000 ct	5000 ct	1250	.125	.075	.70	2000	600	150	2:1	4:1	32.32
71570	81570	20,000 ct	10,000 ct	2500	.125	.075	.70	2000	1200	300	1.41:1	2.83:1	32.32
71575	81575	*20,000 ct	20,000 ct	-	.125	.075	.70	2000	2400	-	1:1	-	37.13
71580	81580	25,000 ct	500 ct	125	.1	.075	.63	2500	60	15	7.07:1	14.14:1	33.53
71585	81585	25,000 ct	1000 ct	250	.1	.075	.63	2500	120	30	5:1	10:1	33.53
71590	81590	30,000 ct	50 ct	12.5	.083	.075	.58	3000	6	1.5	24.5:1	49:1	33.53
71595	81595	30,000 ct	1200 ct	300	.083	.075	.58	3000	144	36	5:1	10:1	33.53
71600	81600	30,000 ct	500 ct	125	.083	.075	.58	3000	60	15	7.75:1	15.5:1	33.53
71605	81605	30,000 ct	200 ct	50	.083	.075	.58	3000	24	6	12.25:1	24.5:1	33.53
71610	81610	30,000 ct	5000 ct	1250	.083	.075	.58	3000	600	150	2.45:1	4.9:1	33.53
71615	81615	30,000 ct	10,000 ct	2500	.083	.075	.58	3000	1200	300	1.73:1	3.46:1	33.53
71620	81620	*30,000 ct	30,000 ct	-	.083	.075	.58	3000	3600	-	1:1	-	36.49
71625	81625	40,000 ct	400 ct	100	.062	.062	.5	4000	48	12	10:1	20:1	36.49

SURFACE MOUNT


SERIES 71000 **SERIES 81000**




SCHEMATICS FOR TRANSFORMERS WITH SPLIT SECONDARIES



SCHEMATIC FOR TRANSFORMERS WITH ELECTROSTATIC SHIELD



SCHEMATIC FOR INDUCTORS



FEATURES

- EXTREME RESISTANCE TO THERMAL SHOCK
- ULTRA MINIATURE SIZE
- PICO IS APPROVED QPL SOURCE (MIL-PRF-27)
- MAGNETIC SHIELD DESIGN AVAILABLE
- ELECTROSTATIC SHIELDING CAN BE ADDED.
- VARIATION OF STANDARD DESIGNS AVAILABLE
- EVERY UNIT IN THIS CATALOG CAN BE MADE WITH A 300 THERMAL CYCLE GUARANTEE USING PICO'S SPECIAL SR CONSTRUCTION. CONTACT FACTORY FOR DETAILS.

*INCLUDES ELECTROSTATIC SHIELD

***Discount Prices: 1-9 Net; 10-24 less 10%; 25-49 less 16%; 50-99 less 23%; 100-499 less 30%

Ordering Instructions:
No minimum. Net 30 days
F.O.B. Pelham, New York

Delivery - stock to one week

INDUCTORS

ALL INDUCTORS HAVE SPLIT WINDINGS AND MEASUREMENTS ARE LISTED FOR BOTH SERIES AND PARALLEL CONNECTIONS. TWO VALUES OF INDUCTANCE, EACH AT A PARTICULAR VALUE OF D.C. CURRENT, ARE LISTED FOR EACH INDUCTOR.

PICO PART NUMBER	PICO PART NUMBER	INDUCTANCE HENRIES	DC CURRENT	DC RESISTANCE	PRICE 1-9***
71705	81705	SERIES { 0.1	4	25	25.69
		PARALLEL { .025	10	6.5	
71710	81710	SERIES { .09	2	105	25.69
		PARALLEL { .23	8	26	
71715	81715	SERIES { 2.5	2	630	25.69
		PARALLEL { 0.6	4	160	
71720	81720	SERIES { 4.5	2	2300	27.28
		PARALLEL { 1.1	4	575	

For immediate engineering assistance or to place an order - Call Toll Free 800-431-1064

PICO Electronics, Inc.

143 Sparks Avenue,
Pelham, NY 10803-1837
FAX 914-738-8225

www.picoelectronics.com
E-Mail: info@picoelectronics.com