



.240 Ring
.031 Electro-Tinned Copper
22-18 AWG (Red)

Spade and Ring Series
Pre-Insulated

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.117	.147	.180						
0	X			B	✓	✓	5000	50118	
		X		B	✓	✓	4000	50118-8	
			X	B	✓	*	4000	50118-8A	
	X			W	✓	✓	5000	50119	
		X		W	✓	✓	4000	50119-8	
			X	W	✓	*	4000	50119-8A	
2	X			B	✓	✓	5000	50126	
		X		B	✓	✓	4000	50126-8	
			X	B	✓	*	4000	50126-8A	
	X			W	✓	✓	5000	50127	
		X		W	✓	✓	4000	50127-8	
			X	W	✓	*	4000	50127-8A	
4	X			B	✓	✓	5000	50134	
		X		B	✓	✓	4000	50134-8	
			X	B	✓	*	4000	50134-8A	
	X			W	✓	✓	5000	50135	
		X		W	✓	✓	4000	50135-8	
			X	W	✓	*	4000	50135-8A	
6	X			B	✓	✓	5000	50142	
		X		B	✓	✓	4000	50142-8	
			X	B	✓	*	4000	50142-8A	
	X			W	✓	✓	5000	50143	
		X		W	✓	✓	4000	50143-8	
			X	W	✓	*	4000	50143-8A	

.300 Ring
.020 Pre-Tinned Brass
22-18 AWG (Red)

Spade and Ring Series
Pre-Insulated

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.117	.147	.180						
4	X			B	✓	✓	5000	50309-200	
		X		B	✓	✓	4000	50309-200-8	
			X	B	✓	*	4000	50309-200-8A	
6	X			B	✓	✓	5000	50321-200	
		X		B	✓	✓	4000	50321-200-8	
			X	B	✓	*	4000	50321-200-8A	
8	X			B	✓	✓	5000	50348-200	
		X		B	✓	✓	4000	50348-200-8	
			X	B	✓	*	4000	50348-200-8A	
10	X			B	✓	✓	5000	50360-200	
		X		B	✓	✓	4000	50360-200-8	
			X	B	✓	*	4000	50360-200-8A	

Recommended Strip Length $\frac{3}{32} \pm \frac{1}{32}$
 * Contact Factory for Latest Agency Approvals.