

samtec

**MOLD-TO-POSITION
PRODUCT**

 Minimums or set-up charges
may apply. Call Samtec.


FOLC-125-02-S-Q-LC

FOLC-120-02-S-Q-P

FOLC-120-02-S-Q

 Surface
SMT
 Mount

.050" x .050" SOCKETS FOLC SERIES

SPECIFICATIONS

 For complete specifications
see www.samtec.com?FOLC

Insulator Material:
Black Liquid Crystal
Polymer

Contact Material: BeCu
Current Rating:
1A @ 80°C ambient
Operating Temp Range:
-55°C to +125°C

Plating:
Au or Sn over
50µ" (1,27µm) Ni
Contact Resistance:
15 mΩ max
Insertion Depth:
(3,30mm) .130" to
(4,06mm) .160"

Insertion Force:
Standard= 5.0oz (1,39N) avg;
LIF= 2.0oz (0,56N) avg.

Normal Force:
Standard= 70 grams
(0,69N) avg; LIF= 40 grams
(0,39N) avg.

Withdrawal Force:
Standard= 4oz (1,11N) avg;
LIF= 1.5oz (0,42N) avg.
Max Cycles:
100 with 10µ" (2,54µm) Au

 Mates with:
MOLC


 Low Insertion Force
contacts available

 High reliability
Tiger-Eye
contacts

IMPORTANT NOTE

 See also ROLC Series for possible
design enhancements, rugged
features and/or cost savings

4
 ROW

 Note: Some sizes, styles and
options are non-standard,
non-returnable.


APPLICATION SPECIFIC OPTION

FOLC

1

NO. PINS
PER ROWLEAD
STYLEPLATING
OPTION

Q

OPTION

 20, 25, 30, 35,
(Call Samtec for other sizes)

 -02
= Surface Mount

 -L2
= Low Insertion
Force Surface
Mount

 -S
or
-SM
= 30µ" (0,76µm)
Gold contact,
Tin (-S) or
Matte Tin (-SM)
on tail







 -LC
= Locking Clip

 -K
(Best Cost Option)
= (6,75mm) .266" DIA
Polyimide film
Pick & Place Pad

 -P
= Plastic Pick &
Place Pad

 -TR
= Tape & Reel

Processing:

Max Processing Temp:
230°C for 60 seconds, or
260°C for 20 seconds 3x
with Matte Sn plating
Lead-Free Solderable:
Yes, with Matte Sn plating
SMT Lead Coplanarity:
(0,15mm) .006" max
Suggested PCB Layouts:
For reference only. Please
contact Samtec or go to
www.samtec.com?FOLC for
recommended PCB layout.


TAPE & REEL AVAILABILITY

 No tooling charges.
125 piece minimum order.
Order any quantity above minimum.
In-house design, manufacture.
Quick turn-around.
Call Samtec for specifications
and ordering information.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047
 SAMTEC FRANCE • Tel: 01 60 95 06 60 • Fax: 01 60 95 06 61
 SAMTEC SCANDINAVIA • Tel: +46-84477280 • Fax: +46-847420413
 SAMTEC CHINA • Tel: 86-21-5385-4089 • Fax: 86-21-5385-4047
 SAMTEC HONG KONG • Tel: 852-26904858 • Fax: 852-26904842
 SAMTEC UK • Tel: 01236 739292 • Fax: 01236 727113
 SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315
 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 • Fax: 65 6841-1502
 SAMTEC TAIWAN • Tel: 886 02 2698-3367 • Fax: 886 02 8698-2159
 SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745
 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299
 SAMTEC ISRAEL • Tel: 972-3-7526600 • Fax: 972-3-7526690
 SAMTEC JAPAN • Tel: 81-424-42-8318 • Fax: 81-424-42-8319
 SAMTEC KOREA • Tel: 823-17175685 • Fax: 823-17175684