

V23030A1021A204 Product Details



V23030A1021A204
(3-1393801-9)

TE Internal Number: 3-1393801-9

 [Active](#)

Communications/Signal PC Board Relays

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

- Product Highlights:**
- V23030 / Card Relay SN Series
 - DC Actuating System
 - Input Voltage = 24 VDC
 - Contact Arrangement = 4 Form C, 4PDT, 4 C/O
 - Contact Current Rating = 2 Amps.

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information

- Product Drawings:**
- None Available

- Catalog Pages/Data Sheets:**
- None Available

- Product Specifications:**
- None Available

- Application Specifications:**
- None Available

- Instruction Sheets:**
- None Available

- CAD Files:**
- None Available

- Additional Information:**
- [Product Line Information](#)

- Related Products:**
- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

- Product Type Features:**
- Termination Type = Through Hole
- Electrical Characteristics:**
- Actuating System = DC
 - Input Voltage (VDC) = 24
 - Contact Current Rating (Amps.) = 2
 - [Coil Resistance \(?\)](#) = 730
 - Coil Power, Nominal (mW) = 780
 - Dielectric Between Coil and Contacts (V rms) = 1000
- Body Related Features:**
- Series = V23030 / Card Relay SN
 - Polarized = No
- Contact Related Features:**
- Mounting Options = PC Board
 - Enclosure = Dust Protected
 - [FCC Part 68 Isolation](#) = No
 - Approved Standards = None
 - Contact Base Material = Hard Gold
 - Approx. Dimensions (L x W x H) (mm [in]) = 39.70 x 32.40 x 10.20 [1.564 x 1.276 x .401]
 - Contact Type = Bifurcated
 - Pin Configuration = Industry Standard

- Configuration Related Features:**
- [Contact Arrangement](#) = 4 Form C, 4PDT, 4 C/O
 - [Coil Magnetic System](#) = Non Polarized, Monostable
 - Coil Suppression Diode = Without
- Industry Standards:**
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
 - [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
 - RoHS/ELV Compliance History = Converted to comply with RoHS directive
- Other:**
- Brand = Axicom

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat with Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage Your Account](#)