
All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.



Tous droits strictement reserves. Reproduction ou communication α des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du propietaire Propriete de c FCI. Droits de reproduction FCI.



PDM: Rev:J


STATUS: Released

All rights strictly reserved. Reproduction or issue to third parties in any Tous droits strictement reserves. Reproduction ou communication a des tiers not permitted without forme que ce soit sans autorisation ecrite Property of FCI. Copyright FCI de c FCI. Droits de reproduction FCI. FC w SEE NOTES CONNECTOR PROFILE Ø0.90-0.05 ₽ NOTES: 3.80 2.FINISH: 4. PRODUCT SPEC: GS-12-174; PACKAGE SPEC: GS-14-873. 3.10033526-N3212XLF MEETS THE EUROPEAN UNION DIRECTIVE AS DESCRIBE 1.MATERIAL SHIELD: IN GS-22-008 AND ITS HSG WILL WITHSTAND EXPOSE TO 260 DEGREE C MYLAR: KAPTON TAPE SHELL: COPPER ALLOY CONTACT: COPPER ALLOY. HOUSING: THERMOPLASTIC. UL 94V-0 RATED, COLOR: BLACK. PEAK TEMPATURE FOR 10 SECONDS IN A IR REFLOW APPLICATION. CONTACT: UNDERPLATED 50u"MIN. NICKEL OVERALL 120u" MIN. 2.50 5.85 GENERAL TOLERANCE +/-0.05mm RECOMMENDED PCB LAYOUT FOR 10033526-XXX1XX CODE L: PLATED BRIGHT TIN/LEAD WITH 120u"THICK. CODE N: PLATED NICKEL WITH 120"THICK BRIGHT TIN/LEAD OR MATTE TIN ON SOLDERING AREA, SELECTIVE GOLD PLATED ON CONTACT AREA. 0.80 OVER 100u" THICKNESS Cu. OVER 100u"THICKNESS Cu. 6.90 ₽ \overline{Z} 2 0.50 0.10 A C 5.45 -c-2.98 REF. 90.90^{+0.05} ф Ø0.10® B® Ģ PRODUCT ORDERING DATA: FOR NON LEAD-FREE 10033526 - X X X X X sheet index mat'l. code ecn no ACAD revision sheet CONNECTOR PROFILE date 1 : Gold Flash. 3 : 30u" Au. 5 : 15u" Au. < -option for shell plating: L: Tin/Lead. N: Nickel. PLATING IN CONTACT AREA: Н 1 : WITH PLASTIC POST.
2 : WITHOUT PLASTIC POST. 1 : HTN.(PA6T) PACKAGING METHOD: HSG MATERIAL: POST OPTION: 5: TRAY PACKAGING TAPE & REEL PACKAGING M: WITH MYLAR BLANK: WITHOUT MYLAR 3.80 engr ALLEN CHANG 9/9/03' chr ROGER LIN 9/9/03' 용 JASMINE CHAING 9/9/03 tolerances unless otherwise specified 5.85 JAMES HSU GENERAL TOLERANCE +/-0.05mm RECOMMENDED PCB LAYOUT FOR 10033526-XXX2X XXX ±.10 .XX ±.20 .x ±.30 0.80 9/9/03' 10033526 - N X X X X M LF FOR LEAD-FREE scale + 6.90 projection CUSTOMER (COPY MM 0.50 0.10 A C 4 size dwg no product family MINI USB B TYPE RECEPTACLE CONNECTOR, 2<u>2526</u> 10033526 П О 5.45 -c-2.98 REF 3 : 30u" Au. PLATING IN CONTACT AREA: POST OPTION:
1: WITH PLASTIC POST.
2: WITHOUT PLASTIC POST. M: WITH MYLAR BLANK: WITHOUT MYLAR LF: Lead Free 2: HTN.(PA46) HSG MATERIAL: PACKAGING METHOD: 2: TAPE & REEL PACKAGING USB R/A SMT TYPE www.tciconnect.com sheet 2 of code ➤ œ

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor. Property of FCI. Copyright FCI.



Tous droits strictement reserves. Reproduction ou communication α des tiers interdite sous quelque forme que ce soit sans autorisation ecrite du propietaire Propriete de c FCI. Droits de reproduction FCI.



PDM: Rev:J

STATUS: Released