

FILTER CHOKES

SMOOTHING CHOKES:

Inductance Tolerance - minus 15 plus 50% at 10 Volts 60 Hz. Lead Terminations

S E C T	Part Number	Inductance (Henries)	DCMA	DC Res OHMS	Insulation Test RMS Volts	Style	Dimensions-Inches					Wt. Lbs.
							Case			Mounting		
							H	W	D	MW	MD	
A	20C50	350.0	5	5500	2000	BAH	2	3¼	1⅞	2⅜⅙	---	1.0
	20C43	20.0	15	900	1500	BAH	1⅞	2⅞	1½	2⅜	---	0.8
	20C180	12.0	30	400	2000	BAH	1⅞	2⅜	1⅜⅙	2	---	0.5
B	20C82	3.5	50	200	2500	BAH	1⅞	2⅞	1½	2⅜	---	0.8
	20C84	7.0	50	550	1500	BAH	1⅞	2⅜	1¼	2	---	0.5
	20C81	7.5	50	400	1500	BAH	1⅞	2⅞	1½	2⅜	---	0.8
	20C66	9.0	50	500	2500	BAH	1⅞	2⅞	1½	2⅜	---	0.8
	26C87	16.0	50	580	1500	BAH	2	3¼	1¾	2⅜⅙	---	1.2
C	20C53	12.0	80	375	2500	BAH	2	3¼	2⅞	2⅜⅙	---	1.5
	26C86	15.0	75	400	1500	BAH	2⅜	3¾	2	3⅞	---	1.5
	20C67	5.0	100	300	2500	TAV	2¾	2¼	2⅞⅙	2⅜	1½	1.5
	26C85	10.5	110	225	3000	BAH	2⅞	4	2¼	3⅞⅙	---	2.2
	26C88	2.5	130	100	2000	BAH	2	3¼	1¾	2⅜⅙	---	1.2
D	26C89	2.3	150	60	2500	BAH	2	3¼	1¾	2⅜⅙	---	1.0
	26C41	1.5	200	90	1500	BAH	1⅞	2⅞	1½	2⅜	---	0.8
	26C91	2.8	300	60	1500	BAH	2⅞	4	2¼	3⅞⅙	---	2.5
E	26C78	1.0	350	35	1500	BAH	2	3¼	2	2⅜⅙	---	1.4
	26C92	0.8	375	25	1500	BAH	2⅜	3¾	2	3⅞	---	1.5
	26C81	0.32	600	10	1500	BAH	2	3¼	2	2⅜⅙	---	1.3

HIGH CURRENT CHOKES:

Inductance measured at 1 Volt, 60 Hz. Lead wire terminations except ■ with lugs.

F	TR-153	3.0mH	1.0A	0.25	1000	BCH-1	1¼	1½	1	1¼	⅞	0.2
	TR-154	11.0mH	1.0A	0.75	1000	BCH-1	1¼	1½	1	1¼	⅞	0.2
	20C00	35.0mH	2.0A	0.75	1500	LAV	2¼	2⅞	2¼	2⅞	2	1.8
	20C26	80.0mH	2.5A	0.61	1500	LAV	3⅞	3⅞	3⅞	2½	3	7.0
		or 20.0mH	5.0A	0.15								
	20C02	10.0mH	8.0A	0.15	1500	LAH	3¼	3¼	3⅞	3⅞	2½	5.3
	20C03	10.0mH	12.5A	0.11	1500	LAH	3⅞	4⅞	3	3⅞	2⅞	6.0
	20C100■	5.0mH	22.5A	0.03	1500	LHH	3⅞	4½	4½	3¼	3½	11.9

MINIATURIZED HIGH CURRENT CHOKES:

Inductance measured at 1 Volt, - 60 Hz. Lead wire terminations

G	20C187	400.0mH	135MA	30	1500	BAH	1¼	2⅞	1⅞	1¼	---	0.3
	20C115	75.0mH	1.0A	2.5	1500	BAH	2	3¼	1¾	2⅞	---	1.0

■ Has lugs

