



- NOTES:
1. TO BE USED WITH PROBE P25-XX26.
 2. MINIMUM CENTRES = 2.54mm.
 3. MATERIAL = BRASS, FINISH = GOLD PLATED.
 4. RECOMMENDED MOUNTING HOLE = $\varnothing 1.70$ mm.
 5. ALL SPECIFICATIONS ARE STATED ON THE PROBE DRAWING P25-XX26.
 6. ALL DIMENSIONS ON S25-526 APPLY TO ALL SLEEVES UNLESS OTHERWISE STATED.

HEIGHT ABOVE PLATE	CONNECTION TYPE			
	CRIMP	SOLDER	TERMINAL	WIRE-WRAP
0.3mm	S25-566	S25-066	S25-466	S25-366
2.5mm	S25-526	S25-036	S25-406	S25-326
5.0mm	S25-536	S25-046	S25-416	S25-336
7.5mm	S25-546	S25-056	S25-426	S25-346

CUSTOMER INFORMATION SHEET

1	14.01.97	----
ISS.	DATE	C/N
APPROVED:		
CHECKED:		
DRAWN: W. BOURNE		
CUSTOMER REF.		
ASSEMBLY DRG:		

OBSOLETE

ORDER CODE:
S25-XX6
SPRING PROBE SLEEVE (SEE DRAWING)

HARWIN

HARWIN INC U.S.A. TEL: (812) 285 0055 FAX: (812) 285 0056	HARWIN PLC U.K. TEL: 01705 370451 FAX: 01705 314590	HARWIN PTE SINGAPORE TEL: 65 7794909 FAX: 65 7793868	HARWIN CONNECTORS KOREA TEL: 822 521 0747 FAX: 822 521 0749
--	--	---	--

TOLERANCES
X. = ±1mm
XX = ±0.25mm
XXX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±1°
UNLESS STATED

MATERIAL:
SEE NOTE 3
FINISH: SEE NOTE 3
S/AREA: mm

TITLE:
2.54mm MIN. CENTRE TWO-PIECE
SPRING PROBE SLEEVE
DRAWING NUMBER:
S25-XX6
SHT 2 OF 2