



## FEATURES

- Tested and Guaranteed as low as 5 ppm/°C Max Tempco
- Wide Operating Range: 50  $\mu$ A - 5 mA
- Low Output Impedance: 0.6  $\Omega$  Typical

## BENEFITS

- Lower Sensitivity to Capacitive Loading
- No Frequency Compensation Required
- Accurate Stable Reference over Temp

## APPLICATIONS

- Building Block for Custom References
- Low Current Voltage Reference for Hand Held Multimeters
- Voltage Reference for Video Flash Converters
- Voltage Reference for D/A and A/D Converters
- Precision Analog Control Circuits

## GENERAL DESCRIPTION

The MP5010 is a 2 terminal, band-gap voltage reference which provides a fixed 1.2 V nominal output voltage. Micro Power Systems design and process enables us to provide guaranteed tempcos as low as 5 ppm/°C max. We provide this with a

wide input current range of 50 $\mu$ A to 5mA, lower sensitivity to load capacitances, and a low output impedance of 0.6 $\Omega$  (typ).


Specified for operation over the commercial (0 to +70°C), industrial (-40 to +85°C), and military (-55 to +125°C) temperature ranges, the MP5010 is available in Plastic TO-92, Metal Can TO-52, and Surface Mount (SOIC) packages.

## ORDERING INFORMATION



Part No.	Max Tempco	Temperature Range	Package Type
MP5010GN	100	-40 to +85°C	Plastic TO-92
MP5010HN	50	-40 to +85°C	Plastic TO-92
MP5010LN	25	-40 to +85°C	Plastic TO-92
MP5010MN	10	0 to 70°C	Plastic TO-92
MP5010JT	100	-55 to +125°C	TO-52
MP5010KT	50	-55 to +125°C	TO-52
MP5010LT	25	-55 to +125°C	TO-52
MP5010MT	10	-40 to +85°C	TO-52
MP5010NT	5	-40 to +85°C	TO-52
MP5010JR	100	-40 to +85°C	SO-8
MP5010GR	100	0 to 70°C	SO-8
MP5010HR	50	-40 to +85°C	SO-8
MP5010LR	25	-40 to +85°C	SO-8
MP5010MR	10	-40 to +85°C	SO-8
MP5010NR	5	-40 to +85°C	SO-8

# MP5010


## PIN CONFIGURATIONS



TO-92 PLASTIC



TO-52 (Metal Can)



8 Lead SOIC: (1.150")

## ELECTRICAL CHARACTERISTICS

Parameter	Symbol	25°C			Tmin to Tmax		Units	Test Conditions/Comments
		Min	Typ	Max	Min	Max		
Reference Current	$I_R$	50		5000			$\mu A$	
Reference Voltage	$V_{REF}$	1.200	1.220	1.250			V	$I_R = 500\mu A$
Output Impedance (1)	$Z_{OUT}$		.6	2			$\Omega$	$I_R = 500\mu A$
RMS Noise Voltage (1)			5				$\mu V$	$10Hz \leq f \leq 10 kHz$ $I_R = 500\mu A$
<b>BREAKDOWN VOLTAGE</b>								
<b>TEMPERATURE COEFFICIENT</b>								
G-S			30	100			ppm/°C	$I_R = 500\mu A$
H-K			25	50				$T_{min} \leq T_A \leq T_{max}$
L			10	25				
M			5	10				
N			3	5				
Reverse Current		50		5000			$\mu A$	To rated specs

## ABSOLUTE MAXIMUM RATINGS (1, 3)

### Maximum Temperature

Storage (JT, KT, LT, MT, NT)	-65 to +200°C
Storage (GN, HN, LN, JR, GR, RR, LR)	-65 to +125°C
Operating Range (JT, KT, LT)	-55 to +125°C
Operating Range (GN, HN, LN, NT, MT, JR, RR, LR)	-40 to +85°C
Operating Range (MN, GR)	0 to 70°C

Lead Temperature (soldering, 10 sec) ..... +260°C

Maximum Power Dissipation (all packages) (2)

Power Dissipation (25°C) ..... 13mW

Maximum Current

Forward Current ..... 10mA

Reverse Current ..... 10mA

### NOTES:

- (1) Guaranteed, not tested.
- (2) Limited by max forward/reverse current.
- (3) Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation at or above this specification is not implied. Exposure to above maximum rating conditions for extended periods may affect device reliability.