


127 Series: | Ø 5 mm LED Vertical PCB Mounting

NEW PRODUCT

- Variable height options
- Low current available
- Blue also available
- MLQ 200
- MTBF 250,000 hrs



Scale 1 : 1
Dimensions in mm (Typical)

Ordering information and technical characteristics (Ta = 25°C)

Order code	Colour	Typ Fwd Voltage Vf @ Iopr	Forward Current Iopr	Luminous Intensity Iv @ Iopr	Wave Length λp	Dimension A ± 0.25	Operating Temp Topr	Storage Temp Tstg
127 - 505 - 04 - 51	Red	2.1	20	33	650	4.8		
127 - 505 - 04 - 52	Red	2.1	20	33	650	6.4		
127 - 505 - 04 - 53	Red	2.1	20	33	650	9.4		
127 - 505 - 04 - 54	Red	2.1	20	33	650	12.7		
127 - 505 - 04 - 55	Red	2.1	20	33	650	15.9		
127 - 505 - 04 - 56	Red	2.1	20	33	650	19.1		
127 - 505 - 04 - 57	Red	2.1	20	33	650	22.2		
127 - 514 - 04 - 51	Green	2.2	20	68	563	4.8		
127 - 514 - 04 - 52	Green	2.2	20	68	563	6.4	- 25	- 25
127 - 514 - 04 - 53	Green	2.2	20	68	563	9.5	to	to
127 - 514 - 04 - 54	Green	2.2	20	68	563	12.7	+ 80	+ 80
127 - 514 - 04 - 55	Green	2.2	20	68	563	15.9		
127 - 514 - 04 - 56	Green	2.2	20	68	563	19.1		
127 - 514 - 04 - 57	Green	2.2	20	68	563	22.2		
127 - 511 - 04 - 51	Yellow	2.2	20	33	585	4.8		
127 - 511 - 04 - 52	Yellow	2.2	20	33	585	6.4		
127 - 511 - 04 - 53	Yellow	2.2	20	33	585	9.5		
127 - 511 - 04 - 54	Yellow	2.2	20	33	585	12.7		
127 - 511 - 04 - 55	Yellow	2.2	20	33	585	15.9		
127 - 511 - 04 - 56	Yellow	2.2	20	33	585	19.1		
127 - 511 - 04 - 57	Yellow	2.2	20	33	585	22.2		
	Diffused	V	mA	mcd	nm	mm	°C	°C