



GROUP J

600 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — 3Ø, 60 Hz

KVA	CATALOG NO.	APPROX. DIMENSIONS Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W - Wall F - Floor	KNOCKOUTS Inches (Cm.)	WEATHER SHIELD P/N	Electrical Connections and Design Figures Begin on Page 42
		HEIGHT	WIDTH	DEPTH					
3.0	T-2A-79330-1S	11.63 (29.5)	12.37 (31.4)	7.47 (19.0)	75 (34.0)	W	0.75-1.25 (1.9-3.2)	NA	28-F
6.0	T-2A-79331-1S	12.55 (31.9)	14.17 (36.0)	8.82 (22.4)	140 (63.5)	W	0.75-1.25 (1.9-3.2)	NA	28-F
9.0	T-2A-79332-1S	15.28 (38.8)	17.77 (45.1)	11.52 (29.3)	180 (81.6)	W	0.75-1.25 (1.9-3.2)	NA	28-F
15.0	T-3-79333-1S	18.86 (47.9)	20.30 (51.6)	9.03 (22.9)	250 (113.0)	F ①	NA	NA	28-J
30.0	T-3-13102-3S	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	325 (147.9)	F ①	NA	WS-A-1	29-E
45.0	T-3-13103-3S	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	400 (181.0)	F ①	NA	WS-A-1	29-E
75.0	T-3-13104-3S	29.90 (75.9)	26.15 (71.5)	22.37 (56.8)	550 (250.0)	F ①	NA	WS-A-2	29-E
112.5	T-2A-13105-3S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	790 (358.0)	F	NA	WS-A-3	29-E
150.0	T-2-13106-3S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	1000 (454.0)	F	NA	WS-A-4	29-E
225.0	T-2-13107-3S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	1250 (567.0)	F	NA	WS-A-4	29-E
300.0	T-2-13099-3S	45.60 (115.8)	36.50 (90.3)	36.50 (90.2)	1550 (703.0)	F	NA	WS-A-5	29-E
NEW 450.0	T-1-13111-3S	62.00 (157.5)	54.00 (137.2)	49.50 (125.7)	2650 (1202.0)	F	NA	WS-B-3	30-G
NEW 500.0	T-1-13112-3S	62.00 (157.5)	54.00 (137.2)	42.00 (106.7)	2675 (1213.0)	F	NA	WS-B-3	30-G
750.0	T-2-13113-4S	62.80 (159.5)	54.00 (137.2)	41.50 (105.4)	4000 (1814.0)	F	NA	WS-A-6	49-E

GROUP K

ENCAPSULATED TRANSFORMERS, 115° C RISE

600 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — 3Ø, 60 Hz

KVA	CATALOG NO.	APPROX. DIMENSIONS Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W - Wall F - Floor	KNOCKOUTS	WEATHER SHIELD P/N	Electrical Connections and Design Figures Begin on Page 42
		HEIGHT	WIDTH	DEPTH					
30.0	T-3-79334-3S	24.61 (63.0)	27.13 (69.0)	11.14 (28.3)	445 (202.0)	F	NA	NA	29-J
45.0	T-3-79335-3S	25.31 (64.3)	30.18 (76.7)	12.76 (32.4)	635 (288.0)	F	NA	NA	29-J
75.0	T-3-79336-3S	26.82 (68.1)	34.68 (88.1)	15.25 (38.7)	930 (422.0)	F	NA	NA	29-J

NEW

GROUP L

600 DELTA PRIMARY VOLTS — 380Y/220 SECONDARY VOLTS — 3Ø, 60 Hz

KVA	CATALOG NO.	APPROX. DIMENSIONS Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W - Wall F - Floor	KNOCKOUTS	WEATHER SHIELD P/N	Electrical Connections and Design Figures Begin on Page 42
		HEIGHT	WIDTH	DEPTH					
3.0	T-2A-79432-1S	11.63 (29.5)	12.37 (31.4)	7.47 (19.0)	75 (34.0)	W	0.75-1.25 (1.9-3.2)	NA	53-F
6.0	T-2A-79433-1S	12.55 (31.9)	14.17 (36.0)	8.82 (22.4)	140 (63.5)	W	0.75-1.25 (1.9-3.2)	NA	53-F
9.0	T-2A-79434-1S	15.28 (38.8)	17.77 (45.1)	11.52 (29.3)	180 (81.6)	W	0.75-1.25 (1.9-3.2)	NA	53-F
15.0	T-3-79435-1S	Consult Factory For Availability							
30.0	T-2A-79436-3S	25.50 (64.8)	24.40 (62.0)	19.40 (49.3)	325 (147.9)	F&W	NA	WS-A-1	50-E
45.0	T-2A-79437-3S	25.50 (64.8)	24.40 (62.0)	19.40 (49.3)	400 (181.0)	F&W	NA	WS-A-1	50-E
75.0	T-2A-79438-3S	29.90 (75.9)	26.15 (71.5)	22.40 (56.9)	550 (250.0)	F	NA	WS-A-2	50-E
112.5	T-2-79439-3S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	750 (340.0)	F	NA	WS-A-3	50-E
150.0	T-2-79440-3S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	1000 (454.0)	F	NA	WS-A-4	50-E
225.0	T-2-79441-3S	41.52 (105.5)	32.90 (83.6)	29.88 (75.9)	1200 (544.0)	F	NA	WS-A-4	50-E
300.0	T-2-79442-3S	45.60 (115.8)	36.50 (90.3)	36.50 (90.3)	1550 (703.0)	F	NA	WS-A-5	50-E
450.0	T-1-79443-3S	62.00 (157.5)	54.00 (137.2)	42.00 (106.7)	2675 (1213.0)	F	NA	WS-B-3	② G
500.0	T-1-79444-3S	62.00 (157.5)	54.00 (137.2)	42.00 (106.7)	2675 (1213.0)	F	NA	WS-B-3	② G

① Wall mounting brackets are available for these sizes, refer to page 50.

② Consult factory for wiring diagram.