






TUBULAR RING TERMINALS

Non-Insulated

- Seamless Tubular Barrel
- Beveled Wire Lead-In
- Double Thick Tongue



Performance Requirements				
Min. Tensile Strength	#8	#6	#4	#2
		90	100	140

PANDUIT® Part Number	Wire Range	Stud Hole	Dimensions in Inches							Std. Pkg. Qty.	Std. Ctn. Qty.	Bulk Pkg. Qty.	Bulk Ctn. Qty.
			Barrel		A	B	G	T	W				
			ID	OD									
S8-10R-Q	8	#10	.18	.27	1.08	.40	.20	.06	.41	25	250	200	800
S8-14R-Q		1/4"	.18	.27	1.16	.40	.28	.06	.46	25	250	200	800
S8-56R-Q		5/16"	.18	.27	1.22	.40	.28	.06	.57	25	250	200	800
S8-38R-Q		3/8"	.18	.27	1.28	.40	.28	.06	.57	25	250	200	800
S6-10R-E	6	#10	.22	.31	1.25	.48	.24	.06	.48	20	200	200	800
S6-14R-E		1/4"	.22	.31	1.28	.48	.24	.06	.48	20	200	200	800
S6-56R-E		5/16"	.22	.31	1.34	.48	.30	.06	.60	20	200	200	800
S6-38R-E		3/8"	.22	.31	1.40	.48	.30	.06	.60	20	200	200	800
S4-10R-E	4	#10	.28	.38	1.39	.48	.28	.07	.55	20	200	200	800
S4-14R-E		1/4"	.28	.38	1.35	.48	.28	.07	.55	20	200	200	800
S4-56R-E		5/16"	.28	.38	1.36	.48	.31	.07	.63	20	200	200	800
S4-38R-E		3/8"	.28	.38	1.38	.48	.31	.07	.63	20	200	200	800
S2-10R-X	2&1	#10	.36	.47	1.68	.59	.35	.08	.69	10	100	200	800
S2-14R-X		1/4"	.36	.47	1.68	.59	.35	.08	.69	10	100	200	800
S2-56R-X		5/16"	.36	.47	1.66	.59	.35	.08	.69	10	100	200	800
S2-38R-X		3/8"	.36	.47	1.66	.59	.35	.08	.69	10	100	200	800
S2-12R-X	1/2"	.36	.47	1.84	.59	.39	.08	.77	10	100	200	800	
S1/0-14R-X	1/0	1/4"	.39	.52	1.83	.58	.38	.10	.76	10	100	100	400
S1/0-56R-X		5/16"	.39	.52	1.83	.58	.38	.10	.76	10	100	100	400
S1/0-38R-X		3/8"	.39	.52	1.83	.58	.38	.10	.76	10	100	100	400
S1/0-12R-X		1/2"	.39	.52	1.97	.58	.41	.10	.81	10	100	100	400
S2/0-14R-X	2/0	1/4"	.45	.58	1.93	.66	.42	.10	.83	10	100	100	400
S2/0-56R-X		5/16"	.45	.58	1.95	.66	.42	.10	.83	10	100	100	400
S2/0-38R-X		3/8"	.45	.58	2.02	.66	.42	.10	.83	10	100	100	400
S2/0-76R-X		7/16"	.45	.58	2.08	.66	.44	.10	.88	10	100	100	400
S2/0-12R-X	1/2"	.45	.58	2.08	.66	.44	.10	.88	10	100	100	400	
S3/0-14R-5	3/0	1/4"	.51	.64	2.11	.83	.47	.10	.94	5	50	100	400
S3/0-56R-5		5/16"	.51	.64	2.09	.83	.47	.10	.94	5	50	100	400
S3/0-38R-5		3/8"	.51	.64	2.16	.83	.47	.10	.94	5	50	100	400
S3/0-76R-5		7/16"	.51	.64	2.17	.83	.47	.10	.94	5	50	100	400
S3/0-12R-5	1/2"	.51	.64	2.17	.83	.47	.10	.94	5	50	100	400	
S4/0-56R-5	4/0	5/16"	.57	.71	2.37	.91	.52	.11	1.03	5	50	100	400
S4/0-38R-5		3/8"	.57	.71	2.37	.91	.52	.11	1.03	5	50	100	400
S4/0-76R-5		7/16"	.57	.71	2.40	.91	.52	.11	1.03	5	50	100	400
S4/0-12R-5		1/2"	.57	.71	2.40	.91	.52	.11	1.03	5	50	100	400
S250-56R-5	250 kcmil	5/16"	.63	.77	2.61	1.01	.56	.12	1.12	5	50	100	—
S250-38R-5		3/8"	.63	.77	2.63	1.01	.56	.12	1.12	5	50	100	—
S250-76R-5		7/16"	.63	.77	2.74	1.01	.56	.12	1.12	5	50	100	—
S250-12R-5		1/2"	.63	.77	2.74	1.01	.56	.12	1.12	5	50	100	—

Order the number of pieces required in multiples of standard package quantities.
 5 = 5 pcs., X = 10 pcs. E = 20 pcs., Q = 25 pcs., C = 100 pcs. and T = 200 pcs. Prime items appear in **BOLD**.

Selection Guide for PANDUIT® Tubular Ring Terminal Installation Tools and Dies

Installation Tools and Dies shown on pages 55 through 60.

PANDUIT Part Number	S8-10R-Q	S8-14R-Q	S8-56R-Q	S8-38R-Q	S6-10R-E	S6-14R-E	S6-56R-E	S6-38R-E	S4-10R-E	S4-14R-E	S4-56R-E	S4-38R-E	S2-10R-X	S2-14R-X	S2-56R-X	S2-38R-X	S2-12R-X	S1/0-14R-X	S1/0-56R-X	S1/0-38R-X	S1/0-12R-X	S2/0-14R-X	S2/0-56R-X	S2/0-38R-X	S2/0-76R-X	S2/0-12R-X	S3/0-14R-5	S3/0-56R-5	S3/0-38R-5	S3/0-76R-5	S3/0-12R-5	S4/0-38R-5	S4/0-76R-5	S4/0-12R-5	S250-56R-5	S250-38R-5	S250-76R-5	S250-12R-5					
	PANDUIT Die Part Number Die Index Number (Number of Crimps)																																										
CT-1700	P21 (2)	P24 (2)	P29 (2)	P37 (3)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—			
CT-720	CD-720-1 P21 (1)	CD-720-1 P24 (1)	CD-720-1 P29 (1)	CD-720-2 P37 (1)	CD-720-2 P42 (1)	CD-720-2 P45 (2)	CD-720-2 P50 (2)	CD-720-3 P54 (2)	CD-720-3 P62 (2)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
CT-930, CT-930CH CT-920, CT-920CH CT-2920, CT-940CH	CD-920-8 P21 (1)	CD-920-6 P24 (1)	CD-920-4 P29 (1)	CD-920-1 P37 (1)	CD-920-1/0 P42 (1)	CD-920-2/0 P45 (1)	CD-920-3/0 P50 (1)	CD-920-4/0 P54 (1)	CD-920-250 P62 (1)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
CT-980, CT-980CH CT-2950, CT-2980	—	—	STD (1)	STD (1)	STD (1)	STD (1)	STD (1)	STD (1)	STD (1)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
CT-2001	CD-2001-8 P21 (1)	CD-2001-6 P24 (1)	CD-2001-4 P29 (1)	CD-2001-1 P37 (1)	CD-2001-1/0 P42 (1)	CD-2001-2/0 P45 (2)	CD-2001-3/0 P50 (2)	CD-2001-4/0 P54 (2)	CD-2001-250 P62 (2)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—