

Butt Type Splices

In butt splices, the wires are butted together and crimped at each end of the splice. They are available either non-insulated, or insulated with nylon


or PVC. Nylon insulated splices meet or exceed the requirements of MIL-T-7928. These splices are color-coded according to wire size.



Nylon Insulated Splices – Aircraft Systems Splices

Cat. No.	Pkg. Qty.	Wire Range	Wt./Lbs. Per 1000	Dimensions	
				A	B
2RZZ	50	26-22	2	1.22	.15
2RAA	50	22-18	6	1.52	.25
RAA23	500	22-18	6	1.52	.25
2RBB	50	16-14	6	1.52	.28
RBB23	500	16-14	6	1.52	.28
2RCC	25	12-10	8	1.89	.35
RCC23	250	12-10	8	1.89	.35

Not U.L. Listed
Installing tools: WT145C, ERG-2001, ERG-2003, WT1452(R22)



Nylon Insulated Splices – Butt Type – Insulation Support

Cat. No.	Pkg. Qty.	Max Ins. Dia.	Wire Range	Wt./Lbs. Per 1000	Dimensions	
					A	B
2RA18	100	.115	22-18	3	1.19	.18
RAA21	1000	.115	22-18	3	1.19	.18
2RB14	100	.148	16-14	3	1.19	.21
RBB21	1000	.148	16-14	3	1.19	.21
2RC10	50	.210	12-10	7	1.26	.28
RCC21	500	.210	12-10	7	1.26	.28
2RD8	25	.340	8	25	1.69	.36
RDD27	200	.340	8	25	1.69	.36
2RE6	20	.420	6	35	1.85	.45
REE28	200	.420	6	35	1.85	.45
2RF4	15	.510	4	40	1.85	.52

U.L. Listed E9809
Installing tools: ERG-2001, ERG-2003, WT145C, WT112M, TBM6/TBM6S (D-F)
Note: Not available on Mylar Tape.

