

L-483		L-433		L-323		L-362	
-------	--	-------	--	-------	--	-------	--

Part No.	Emitting Color + Material	λ_D (nm)	Lens Type	Iv (mcd) @10mA *20mA		Viewing Angle	Dimension
				Min.	Typ.		

L-483HDT	GaP	660	red diffused	0.5	1	100°	T-1 3/4 (5mm) Cylindrical L-483SRSGW SR 1 2 SG
L-483IDT	GaAsP/GaP	625	red diffused	2	5	100°	
L-483EDT	GaAsP/GaP	625	orange diffused	3	7	100°	
L-483GDT	GaP	568	green diffused	1	4	100°	
L-483YDT	GaAsP/GaP	588	yellow diffused	1	4	100°	
L-483SRSGW	GaAlAs	640	white diffused	*20	*50	80°	
	GaP	568		*5	*10		

L-433HDT	GaP	660	red diffused	0.7	1	100°	T-1 3/4 (5mm) Spiral Round
L-433IDT	GaAsP/GaP	625	red diffused	3	8	100°	
L-433EDT	GaAsP/GaP	625	orange diffused	3	8	100°	
L-433GDT	GaP	568	green diffused	2	5	100°	
L-433YDT	GaAsP/GaP	588	yellow diffused	2	4	100°	
L-433SRDT	GaAlAs	640	red diffused	*50	*100	100°	

L-323HD	GaP	660	red diffused	0.5	1	100°	5.6mm x 4.9mm Triangular
L-323ID	GaAsP/GaP	625	red diffused	3	8	100°	
L-323ED	GaAsP/GaP	625	orange diffused	3	8	100°	
L-323GD	GaP	568	green diffused	2	4	100°	
L-323YD	GaAsP/GaP	588	yellow diffused	2	4	100°	

L-362HD	GaP	660	red diffused	0.5	0.8	100°	3mm x 4.5 mm Triangular
L-362ID	GaAsP/GaP	625	red diffused	1	3	100°	
L-362GD	GaP	568	green diffused	1	2	100°	
L-362YD	GaAsP/GaP	588	yellow diffused	1	2	100°	

NOTES :

1. All dimensions are in millimeters (inches)
2. Tolerance is $\pm 0.25\text{mm}$ (0.01") unless otherwise noted.