

Part Number: E3602S

Revision Level: 10

Date: 1/21/2009

2C 18 SOLID BC FLEX OAS FLEX

Fire Alarm/Life Safety Cable

A. CONSTRUCTION

Conductor:	#18 AWG Solid Bare Copper	0.040" nom.
Insulation:	0.008" Wall FLEXGUARD*	0.056" nom.
Cable:	2C @ 2.25" LHL with AL / PE & # 22 7/30 TC DW	0.117" nom.
Jacket:	0.015" Wall FLEXGUARD*	0.147" +/- 0.008"
Print Legend:	<i>CAROL A (R) 18 AWG - - E3602S - - 75C TYPE FPLP E66267-8 (UL) - - MADE IN USA (DATE CODE & REVERSE SEQUENTIAL FOOTAGE)</i>	

DIAMETERS

B. INDUSTRY APPROVALS

National Electrical Code	Article 760
UL Standard 1424	Type FPLP

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (V _{rms}):	300V
CONDUCTOR D.C. RESISTANCE:	6.4 Ohms/1000 ft nom
SHIELD RESISTANCE:	6.2 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	65.7 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	118.2 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	31 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.