

# General Cable Product Data Sheet

Part Number: E3622S

Revision Level: 8

Date: 10/26/2007

**2C 14 SOLID BC FLEX OAS FLEX**

**Fire Alarm/Life Safety Cable**

## **A. CONSTRUCTION**

Conductor:	#14 AWG Solid Bare Copper	0.064" nom.
Insulation:	0.012" Wall FLEXGUARD*	0.088" nom.
Cable:	2C @ 2.50" LHL with AL / PE & # 18 AWG 16/30 TC DW	0.180" nom.
Jacket:	0.015" Wall FLEXGUARD* - Red	0.210" +/- 0.011"
Print Legend:	<b>CAROL (R) 14 AWG - - E3622S - - 75C TYPE FPLP E66267-8 (UL) - - MADE IN USA (DATE CODE &amp; SEQUENTIAL FOOTAGE 1000' TO 0')</b>	

## **DIAMETERS**

## **B. INDUSTRY APPROVALS**

National Electrical Code	Article 760
UL Standard 1424	Type FPLP

## **C. ELECTRICAL PROPERTIES**

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (V <sub>rms</sub> ):	300V
CONDUCTOR D.C. RESISTANCE:	2.5 Ohms/1000 ft nom
SHIELD RESISTANCE:	4.2 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	68.02 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	122.44 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	29.9 Ohms @ 1MHz nom

## **D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

\*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.