



## Specifications

Expansion Interface	1 x MiniPCI slot 1 x PC/104 slot
Touchscreen	Resistive type
Power Supply	24VDC, 55W, w/ fuse power protection
Dimensions	208.5 mm (8.21 ") (W) x 59.5 mm (2.34 ") (D) x 167.3 mm (6.59 ") (H)
Packing Dimensions	340 mm (13.39") (W) x 100 mm (3.94") (D) x 230 mm (9.06") (H)
Weight (net/gross)	1.3 kg (2.87 lb)/2 kg (4.4 lb)
Environment	Operating temperature: 0° ~ +50°C (32°F ~ 122°F) (in airflow condition) 0° ~ +45°C (32°F ~ 113°F) Storage Temperature: -20°C ~ +80°C (-4°F ~ +176°F) Relative humidity: 10% ~ 95% @ 40°C; non-condensing Operation vibration (w/o expansion): 2G, 5 ~ 500Hz, random for CompactFlash
Certification	CE

## Ordering Information

GOT-3570T	5.7" QVGA TFT compact fanless touch panel computer
E223570102	1 x PC/104 slot
E223570103	2 x PC/104 slot
50966A23040E	Power adapter, 70W, 110-230VAC to 24VDC
Wireless kit	802.11 b/g wireless LAN kit

\* Specification and certifications are based on options and may vary.

## Optional EOS Installation

Windows® CE.NET

Overview

Industrial Panel  
Computers &  
Monitors

Heavy-duty  
Fanless Touch  
Panel Computers

Digital  
Signage  
Solutions

Healthcare  
& Medical  
Solutions

Open Frame  
Panel  
Computers

Accessories

## Dimensions

