

Part Number: C4408ST

Revision Level: 0

Date: 11/5/2007

2C 22 7/.0096 BC PVC NS PVC

Sound, Alarm & Security Cable

A. CONSTRUCTION

Conductor: #22 AWG 7/.0096 Stranded Bare Copper
 Insulation: 0.007" Wall Polyvinyl Chloride
 Cable: 2C @ 4.00" LHL
 Jacket: 0.020" Wall Polyvinyl Chloride – Beige
 Print Legend: *CAROL A (R) CMX OUTDOOR-CMR (UL) C(UL) – SW – 22 AWG E111240-8 (DATE CODE + SEQ FT)*

DIAMETERS

0.029" nom.
 0.043" nom.
 0.085" nom.
 0.125" +/- 0.006"

B. INDUSTRY APPROVALS

National Electrical Code
 UL Standard 444

Article 800
 Type CMX/CMR

C. ELECTRICAL PROPERTIES

TEMPERATURE: 60C
 SUGGESTED WORKING VOLTAGE (V_{rms}): 300V
 CONDUCTOR D.C. RESISTANCE: 16.6 Ohms/1000 ft nom
 MUTUAL CAPACITANCE: 39.12 pF/ft @ 1kHz nom
 CHARACTERISTIC IMPEDANCE: 57.9 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Red
2	Green