

Ambient Light Sensor


GA1A1S203WP

Features

- Logarithmic output
- Thinnest in the industry with a compact package (1.6 × 2.0 × 0.42 mm)
- Stable output current over the specified temperature range
- Adapted to human eye sensitivity
- Integrated photo-diode and amplifier circuit
- Reflow soldering/lead-free

Sensitivity characteristics

Adapted to human eye sensitivity



Main Specifications


Applications

Items	Symbol	Specifications	Condition
Supply voltage	Vcc	2.3 to 3.2 V	
Dissipation current	Icc	TYP. 70 μA	Vcc = 2.9 V, Ev = 1 000 lx
Output current	Io	TYP. 20 μA	Ev = 100 lx
Specified temperature	—	0.25%/ °C	-30 °C to +70 °C, Ev = 1 000 lx
Output accuracy	—	MAX. ±20%	—
Peak sensitivity wavelength	λ	555 nm	—
Response time	tr, tf	MAX. 150 μs	Vcc = 2.9 V, Ev = 100 to 55 000 lx, R = 27 kΩ
Operating temperature	Topr	-40 to +85 °C	



• Mobile phones

Outline Dimensions



■ Under copyright laws, no part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical for any purpose, in whole or in part, without the express written permission of SHARP.
 ■ SHARP reserves the right to make changes in the contents described herein at any time without notice. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.