


MOS FET Relays

G3VM-401A/D

Analog-switching MOS FET Relays with 400-V Load Voltage

- A 4-pin Relay in the 400-V load voltage series.
- Continuous load current of 120 mA.
- Dielectric strength of 2,500 Vrms between I/O.
- RoHS Compliant.



Note: The actual product is marked differently from the image shown here.

■ Application Examples

- Measurement devices
- Security systems
- Amusement machines

■ List of Models

Contact form	Terminals	Load voltage (peak value)	Model	Number per stick	Number per tape
SPST-NO	PCB terminals	400 VAC	G3VM-401A	100	---
	Surface-mounting terminals		G3VM-401D		
			G3VM-401D(TR)	---	1,500

■ Dimensions

Note: All units are in millimeters unless otherwise indicated.

G3VM-401A



Note: The actual product is marked differently from the image shown here.


G3VM-401D




Note: The actual product is marked differently from the image shown here.

■ Terminal Arrangement/Internal Connections (Top View)

G3VM-401A




G3VM-401D




■ PCB Dimensions (Bottom View)

G3VM-401A



■ Actual Mounting Pad Dimensions (Recommended Value, Top View)

G3VM-401D



■ Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)


Item	Symbol	Rating	Unit	Measurement conditions
Input	LED forward current	I_F	50	mA
	Repetitive peak LED forward current	I_{FP}	1	A
	LED forward current reduction rate	$\Delta I_F/\text{°C}$	-0.5	mA/°C
	LED reverse voltage	V_R	5	V
	Connection temperature	T_j	125	°C
Output	Load voltage (AC peak/DC)	V_{OFF}	400	V
	Continuous load current	I_O	120	mA
	ON current reduction rate	$\Delta I_{ON}/\text{°C}$	-1.2	mA/°C
	Connection temperature	T_j	125	°C
Dielectric strength between input and output (See note 1.)	V_{I-O}	2,500	V_{rms}	AC for 1 min
Operating temperature	T_a	-40 to +85	°C	With no icing or condensation
Storage temperature	T_{stg}	-55 to +125	°C	With no icing or condensation
Soldering temperature (10 s)	---	260	°C	10 s

Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.

■ Electrical Characteristics ($T_a = 25^\circ\text{C}$)

Item	Symbol	Minimum	Typical	Maximum	Unit	Measurement conditions
Input	LED forward voltage	V_F	1.0	1.15	1.3	V
	Reverse current	I_R	---	---	10	μA
	Capacity between terminals	C_T	---	30	---	pF
	Trigger LED forward current	I_{FT}	---	1	3	mA
Output	Maximum resistance with output ON	R_{ON}	---	18	35	Ω
	Current leakage when the relay is open	I_{LEAK}	---	0.0008	1.0	μA
	Capacity between terminals	C_{OFF}	---	40	---	pF
Capacity between I/O terminals	C_{I-O}	---	0.8	---	pF	$f = 1 \text{ MHz}$, $V_s = 0 \text{ V}$
Insulation resistance	R_{I-O}	1,000	---	---	$M\Omega$	$V_{I-O} = 500 \text{ VDC}$, $R_{OH} \leq 60\%$
Turn-ON time	t_{ON}	---	0.4	1.0	ms	$I_F = 5 \text{ mA}$, $R_L = 200 \Omega$, $V_{DD} = 20 \text{ V}$ (See note 2.)
Turn-OFF time	t_{OFF}	---	0.09	1.0	ms	

Note: 2. Turn-ON and Turn-OFF Times




■ Recommended Operating Conditions

Use the G3VM under the following conditions so that the Relay will operate properly.

Item	Symbol	Minimum	Typical	Maximum	Unit
Load voltage (AC peak/DC)	V_{DD}	---	---	320	V
Operating LED forward current	I_F	5	7.5	25	mA
Continuous load current (AC peak/DC)	I_O	---	---	100	mA
Operating temperature	T_a	-20	---	65	°C

■ Engineering Data



All sales are subject to Omron Electronic Components LLC standard terms and conditions of sale, which can be found at http://www.components.omron.com/components/web/webfiles.nsf/sales_terms.html

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.

To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.



**OMRON ELECTRONIC
COMPONENTS LLC**
55 E. Commerce Drive, Suite B
Schaumburg, IL 60173

847-882-2288

Cat. No. X302-E-1

12/10

Specifications subject to change without notice

OMRON ON-LINE

Global - <http://www.omron.com>
USA - <http://www.components.omron.com>

Printed in USA