

<p>0512</p> <p>0512-0-15-XX-12-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>2218</p> <p>2218-0-15-XX-22-XX-10-0 Press-fit in 1,45 mounting hole</p>	<p>0703</p> <p>0703-0-15-XX-12-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>0574</p> <p>0574-0-15-XX-12-XX-04-0 Press-fit in 1,45 mounting hole</p>
<p>0468</p> <p>0468-0-15-XX-12-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>0550</p> <p>0550-0-15-XX-22-XX-10-0 Solder mount in 1,32 min. mounting hole</p>	<p>0671</p> <p>0671-0-15-XX-12-XX-10-0 Solder mount in 1,6 min. mounting hole</p>	<p>0707</p> <p>0707-0-15-XX-12-XX-10-0 Solder mount in 1,3 min. mounting hole</p>
<p>5739</p> <p>5739-0-18-XX-12-XX-10-0 Surface mount Also available on 16mm wide carrier tape: 3,000 parts per 330mm reel. Order as: 5739-0-58-XX-12-XX-10-0</p>	<p>8894</p> <p>8894-0-15-XX-12-XX-10-0 Hex press-fit in 1,5 plated thru hole</p>	<p>1534</p> <p>1534-0-15-XX-12-XX-04-0 Press-fit in 1,42 mounting hole</p>	

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY</p> <p>TOLERANCES ON: LENGTHS: ± 0,13 DIAMETERS: ± 0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 1X - XX - XX - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL 80 5,08µm TIN OVER NICKEL ◊ 15 0,25µm GOLD OVER NICKEL ◊</p> <p>SPECIFY CONTACT FINISH: →</p> <p>02 2,54µm TIN/LEAD OVER NICKEL 84 2,54µm TIN OVER NICKEL ◊ 27 0,76µm GOLD OVER NICKEL ◊</p> <p>SELECT CONTACT #12 or #22 CONTACT (DATA ON PAGE 207)</p>
--	---