

• Products

- O By Type
 - Connectors
 - Electromechanical Components
 - Electronic Modules
 - Fiber Optics
 - Filters
 - Identification & Labeling
 - Passive Components
 - Power Sources
 - RF & Microwave Products
 - Tooling Products
 - Touch Screen Displays
 - Tubing, Molded and Harnessing Products
 - Wire, Cable and Cable Assemblies
 - List all product types...
- O <u>By Industry</u>
 - Aerospace & Defense Products
 - Appliance
 - Automotive
 - Mutomotive
 - Communications
 - Computer & Consumer Electronics
 - Industrial & Commercial
 - Instrumentation & Medical
- O By Brand
- O A to Z
- O <u>Product News</u>

• **Documentation**

- O Find Documents & Drawings
- O Find CAD Models
- O SPICE/Electrical Models
- O NAFTA Certificate of Origin
- O White Papers

Resources

- O RoHS Compliance & Alternates
- O Cross Reference Products
- O Compare Multiple Products
- O Check Distributor Inventory
- O Find Authorized Distributors


• My Account

- O Sign In
- O Register

• Customer Support

- O Support
- O RoHS Support Center
- O Glossary of Terms
- O eBulletin Newsletter

KUP93-14D13-12 Product Details



KUP93-14D13-12<u>Active</u>

Mid-Range Plug-in/Panel Mount General Purpose Relays



Product Highlights:

- KUP93 Series
- Contact Arrangement = 3 Form C, 3PDT, 3 C/O
- Contact Current Rating = 5 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

View all Features | Find Similar Products

Find Similar Froducts

Previous 1 ... 11 12 13 14 [15] ... 20 Next Quick Links

- Check Pricing & Availability
 - Search for Tooling
 - Product Feature Selector
 - Compare Products
 - Contact Us About This Product

Documentation & Additional Information

Product Drawings:

• None Available

Catalog Pages/Data Sheets:

• KUP93 General Purpose 3 to 10 Amp, Multicontact AC o... (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Additional Product Images:

- Schematic
- Wiring Diagram

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

• <u>Termination Type</u> = .187 x .020 Quick Connect Terminals

Electrical Characteristics:

- Contact Current Rating (Amps.) = 5
- Coil Resistance (?) = 120
- Actuating System = DC
- <u>Coil Power, Nominal (W)</u> = 1.20
- <u>Input Voltage (VDC)</u> = 12

Body Related Features:

- <u>Series</u> = KUP93
- Polarized = No

Contact Related Features:

- Mounting Options = Plain Case
- <u>Enclosure</u> = Enclosed
- FCC Part 68 Isolation = No
- Relay Type = General
- <u>Contact Material</u> = Silver
- Approx. Dimensions (L x W x H) (mm[in]) = 38.90 x 35.70 x 48.40 [1.532 x 1.406 x 1.907]
- Wiring Diagram= 3 FormC
- Approved Standards = UL Recognized, CSA Certified

Configuration Related Features:

- Contact Arrangement = 3 Form C, 3PDT, 3 C/O
- <u>Coil Magnetic System</u> = Monostable
- <u>Coil Suppression Diode</u> = Without
- Coil Selection Criteria = Nominal Voltage
- Coil Latching = Without
- <u>LED Indicator</u> = Without

Industry Standards:

- RoHS/ELV Compliance = RoHS/Not ELV Compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives

Other:

Brand = Potter & Brumfield