



SPN4402

N-Channel Enhancement Mode MOSFET

DESCRIPTION

The SPN4402 is the N-Channel logic enhancement mode power field effect transistors are produced using high cell density , DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance.

These devices are particularly suited for low voltage application , notebook computer power management and other battery powered circuits where high-side switching .



FEATURES

- ◆ 30V/12A, $R_{DS(ON)}= 13m\Omega @ V_{GS}= 10V$
- ◆ 30V/10A, $R_{DS(ON)}= 18m\Omega @ V_{GS}= 4.5V$
- ◆ Super high density cell design for extremely low $R_{DS(ON)}$
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ SOP – 8P package design

APPLICATIONS

- Power Management in Note book
- Battery Powered System
- DC/DC Converter
- Load Switch
- LCD Display inverter

PIN CONFIGURATION(SOP – 8P)



PART MARKING



A : Lot Code
B : Date Code



SPN4402

N-Channel Enhancement Mode MOSFET

PIN DESCRIPTION

Pin	Symbol	Description
1	S	Source
2	S	Source
3	S	Source
4	G	Gate
5	D	Drain
6	D	Drain
7	D	Drain
8	D	Drain

ORDERING INFORMATION

Part Number	Package	Part Marking
SPN4402S8RGB	SOP- 8P	SPN4402

※ SPN4402S8RGB : 13" Tape Reel ; Pb – Free ; Halogen – Free

ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V _{DSS}	30	V
Gate –Source Voltage	V _{GSS}	±20	V
Continuous Drain Current(T _J =150°C)	T _A =25°C	ID	A
	T _A =70°C		
Pulsed Drain Current	I _{DM}	30	A
Continuous Source Current(Diode Conduction)	I _S	2.3	A
Power Dissipation	T _A =25°C	P _D	W
	T _A =70°C		
Operating Junction Temperature	T _J	-55/150	°C
Storage Temperature Range	T _{STG}	-55/150	°C
Thermal Resistance-Junction to Ambient	R _{θJA}	80	°C/W



SPN4402

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)


Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, ID=250uA	30			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , ID=250uA	1.0		3.0	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =24V, V _{GS} =0V			1	uA
		V _{DS} =24V, V _{GS} =0V T _J =55°C			5	
On-State Drain Current	I _{D(on)}	V _{DS} ≥5V, V _{GS} =10V	25			A
Drain-Source On-Resistance	R _{DSS(on)}	V _{GS} = 10V, ID=12A		0.010	0.013	Ω
		V _{GS} =4.5V, ID=10A		0.013	0.018	
Forward Transconductance	g _{fs}	V _{DS} =15V, ID=6.2A		13		S
Diode Forward Voltage	V _{SD}	I _S =2.3A, V _{GS} =0V		0.5	1.0	V
Dynamic						
Total Gate Charge	Q _g	V _{DS} =15V, V _{GS} =10V ID= 2A		10	18	nC
Gate-Source Charge	Q _{gs}			2.8		
Gate-Drain Charge	Q _{gd}			2.0		
Input Capacitance	C _{iss}	V _{DS} =15V, V _{GS} =0V f=1MHz		850		pF
Output Capacitance	C _{oss}			158		
Reverse Transfer Capacitance	C _{rss}			120		
Turn-On Time	t _{d(on)}	V _{DD} =15V, R _L =15Ω ID=5.0A, V _{GEN} =10V R _G =1Ω		10	15	nS
	t _r			4	12	
Turn-Off Time	t _{d(off)}			15	30	
	t _f			10	15	




SPN4402

N-Channel Enhancement Mode MOSFET


TYPICAL CHARACTERISTICS




V_{DS} - Drain-to-Source Voltage (V)
Output Characteristics



V_{GS} - Gate-to-Source Voltage (V)
Transfer Characteristics



On-Resistance vs. Drain Current and Gate Voltage







V_{DS} - Drain-to-Source Voltage (V)
Capacitance



SPN4402

N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS








SPN4402

N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS






SPN4402

N-Channel Enhancement Mode MOSFET

SOP-8 PACKAGE OUTLINE



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270 (BSC)		0.050 (BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°



SPN4402

N-Channel Enhancement Mode MOSFET

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation

©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1, Park Street

NanKang District (NKSP), Taipei, Taiwan 115

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

©<http://www.syncpower.com>