


Single Phase Bridge Modules EH60, EH75



Dim.	Inches		Millimeter		Notes
	Minimum	Maximum	Minimum	Maximum	
A	—	1.10	—	27.94	
B	2.25	2.40	57.15	60.96	
C	.930	.950	23.62	24.13	
D	1.740	1.760	44.19	44.70	
E	1.883	1.887	47.82	47.92	
F	.495	.505	12.57	12.83	
G	.325	.335	8.25	8.50	
H	.215	.225	5.46	5.71	
J	1.270	1.300	32.25	33.02	
K	.198	.208	5.02	5.28	Dia.
L	1.055	1.075	26.79	27.30	
M	#10-32 Tapped Holes				

Microsemi Catalog Number

EH6002B*	EH7502B*
EH6004B*	EH7504B*
EH6006B*	EH7506B*
EH6008B*	EH7508B*
EH6010B*	EH7510B*
EH6012B*	EH7512B*

Repetitive Peak Reverse Voltage

200
400
600
800
1000
1200

*Add S for Transient Suppressor across output

- Integral Transient Suppression Available
- High Terminal-to-base Isolation
- Available to 1200V
- Mounting Bolts Isolated From Power Terminals

Electrical Characteristics

		<u>EH60</u>	<u>EH75</u>	
Maximum DC output current, single phase	I_o	60A	75A	$T_C = 113^\circ\text{C}$
Maximum surge current per diode	I_{FSM}	1050A	1500A	8.3ms, half sine, $T_J = 175^\circ\text{C}$
Max. I^2t for fusing	I^2t	4600A ² S	9300A ² S	
Max. peak forward voltage per diode	V_{FM}	1.2V	1.1V	@ I_o ; $T_J = 25^\circ\text{C}$ *
Max. peak reverse current per diode	I_{RM}	—	4mA	V_{RRM} , $T_J = 150^\circ\text{C}$
Max. peak reverse current per diode	I_{RM}	—	20 μA	V_{RRM} , $T_J = 25^\circ\text{C}$
Minimum isolation voltage	V_{ISOL}	1500V _{RMS}		any terminal-to-base

*Pulse Test: Pulse width 300 μsec duty cycle 2 %

Thermal and Mechanical Characteristics

Storage temp range	T_{STG}	-55°C to 175°C
Operating junction temp range	T_J	-55°C to 175°C
Max thermal resistance per diode	EH60 R θ_{JC}	1.0°C/W Junction to case
	EH75 R θ_{JC}	0.85°C/W Junction to case
Mounting torque		25-30 lb-in
Typical thermal resistance (greased)	R θ_{CS}	0.07°C/W Case to sink
Typical Weight		5.8 ounces (165 grams)



SCOTTSDALE

8700 East Thomas Road, P.O. Box 1390
Scottsdale, AZ 85252
PH: (480) 941-6300
FAX: (480) 947-1503
www.microsemi.com

05-01-07 Rev. 3

EH60, EH75

Figure 1
Typical Forward Characteristics – Per Diode




Figure 3
Maximum Nonrepetitive Surge Current – Per Diode




Figure 2
Forward Current Derating

