

ELECTRONIC / GLASS FUSES



STGS / STGS-V

Glass Body
 Indicating Time Delay
 4.5 x 14.5mm 2AG
 1-1/2" Axial Leads Optional

1/4A through 3-1/2A, 250VAC - UL Listed and CSA Certified
 4A through 7A, 125VAC - UL Recognized
 STGS-V Available on tape and reel



3ABS / 3ABSRI

Ceramic Body
 Indicating Fast Action
 4.5 x 14.5mm 2AG
 1-1/2" Axial Leads Optional

3/4A through 16A, 125VAC - UL Listed
 Indicating pin extends a minimum 3/16" from the end of the fuse when the fuse operates.

Standard Fuse Ampere Ratings

CATALOG NUMBER	AXIAL LEAD CAT. NO.	AMPERE RATING	VOLTS	I.R.
STGS1/4	STGS-V1/4	1/4A	250V	1
STGS3/8	STGS-V3/8	3/8A	250V	1
STGS1/2	STGS-V1/2	1/2A	250V	1
STGS6/10	STGS-V6/10	6/10A	250V	1
STGS3/4	STGS-V3/4	3/4A	250V	1
STGS8/10	STGS-V8/10	8/10A	250V	1
STGS1	STGS-V1	1A	250V	1
STGS1-1/4	STGS-V1-1/4	1-1/4A	250V	2
STGS1-1/2	STGS-V1-1/2	1-1/2A	250V	2
STGS2	STGS-V2	2A	250V	2
STGS2-1/4	STGS-V2-1/4	2-1/4A	250V	2
STGS2-1/2	STGS-V2-1/2	2-1/2A	250V	2
STGS3	STGS-V3	3A	250V	2
STGS3-1/2	STGS-V3-1/2	3-1/2A	250V	2
STGS4	STGS-V4	4A	125V	3
STGS5	STGS-V5	5A	125V	3
STGS6	STGS-V6	6A	125V	3
STGS7	STGS-V7	7A	125V	3

1. 250VAC @ 35A I.R./125VAC @ 10kA I.R.
2. 250VAC @ 100A I.R./125VAC @ 10kA I.R.
3. 125VAC @ 400A I.R.

Standard Fuse Ampere Ratings

CATALOG NUMBER	RED PIN * CAT. NO.	AMPERE RATING	VOLTS	I.R.
3ABS13/4	3ABSRI3/4	3/4A	125V	1
3ABS11	3ABSRI1	1A	125V	1
3ABS11-1/2	3ABSRI1-1/2	1-1/2A	125V	1
3ABS12	3ABSRI2	2A	125V	1
3ABS13	3ABSRI3	3A	125V	1
3ABS14	3ABSRI4	4A	125V	1
3ABS15	3ABSRI5	5A	125V	1
3ABS16	3ABSRI6	6A	125V	1

1. 125VAC @ 10kA I.R.

*3ABSRI indicating pin is red, 3ABS1 indicating pin is silver plated