

<h3>5062</h3> <p>5062-0-00-XX-00-00-33-0 Solder mount in .029 mounting hole</p>	<h3>8451</h3> <p>8451-0-00-XX-00-00-33-0 Solder mount in .029 mounting hole</p>	<h3>6477</h3> <p>6477-0-00-XX-00-00-38-0 Solder mount in .034 mounting hole</p>	<h3>4477</h3> <p>4477-0-00-XX-00-00-33-0 Solder mount in .034 mounting hole</p>
--	--	--	--

<h3>4268</h3> <p>4268-0-00-XX-00-00-33-0 Solder mount in .039 mounting hole</p>	<h3>9086</h3> <p>9086-0-00-XX-00-00-33-0 Solder mount in .040 mounting hole</p>	<h3>8330</h3> <p>8330-0-00-XX-00-00-38-0 Solder mount in .044 mounting hole</p>	<h3>9228</h3> <p>9228-0-00-XX-00-00-38-0 Solder mount in .044 mounting hole</p>
--	--	--	--

<h3>6095</h3> <p>6095-X-00-XX-00-00-38-0 Solder mount in .044 mounting hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Pin Length L</th> </tr> </thead> <tbody> <tr> <td>6095-0</td> <td>.580</td> </tr> <tr> <td>6095-1</td> <td>.475</td> </tr> </tbody> </table>	Basic Part Number	Pin Length L	6095-0	.580	6095-1	.475	<h3>6092</h3> <p>6092-0-00-XX-00-00-33-0 Solder mount in .044 mounting hole</p>
Basic Part Number	Pin Length L							
6095-0	.580							
6095-1	.475							

<p>SPECIFICATIONS</p> <p>PIN MATERIAL: Brass Alloy 360, 1/2 Hard (Except where noted)</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 00 - XX - 00 - 00 - XX - 0</p> <p>BASIC PART # →</p>	<p>SPECIFY PIN FINISH:</p> <ul style="list-style-type: none"> 01 200μ" TIN/LEAD OVER NICKEL ◇ 80 200μ" TIN OVER NICKEL (RoHS) ◇ 15 10μ" GOLD OVER NICKEL (RoHS) ◇ 21 20μ" GOLD OVER NICKEL (RoHS) ◇ 34 50μ" GOLD OVER NICKEL (RoHS)