

**FEATURES**

Epitaxial planar die construction.

Ideal for medium power amplification and switching.


**MMBT2907 (PNP)**


MAXIMUM RATINGS (TA=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	$V_{CBO}$	-60	V
Collector-Emitter Voltage	$V_{CEO}$	-40	V
Emitter-Base Voltage	$V_{EBO}$	-5	V
Collector Current -Continuous	$I_C$	-600	mA
Collector Power Dissipation	$P_C$	350	mW
Thermal Resistance Junction to Ambient	$R_{JA}$	360	°C/W
Junction Temperature	$T_J$	150	°C
Storage Temperature	$T_{stg}$	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{CBO}$	$I_C=-10\mu A$ $I_E=0$	-60			V
Collector-emitter breakdown voltage	$V_{CEO}$	$I_C=-10mA$ $I_B=0$	-40			V
Emitter-base breakdown voltage	$V_{EBO}$	$I_E=-10\mu A$ $I_C=0$	-5			$\mu V$
Collector cut-off current	$I_{CBO}$	$V_{CB}=-50V$ $I_E=0$			-0.02	$\mu A$
Collector cut-off current	$I_{CEX}$	$V_{CE}=-30V$ $V_{BE(OFF)}=-0.5V$			-0.05	$\mu A$
DC current gain	$h_{FE}$	$V_{CE}=-10V$ $I_C=-150mA$	100		300	
		$V_{CE}=-10V$ $I_C=-0.1mA$	35			
		$V_{CE}=-10V$ $I_C=-1mA$	50			
		$V_{CE}=-10V$ $I_C=-10mA$	75			
		$V_{CE}=-10V$ $I_C=-500mA$	30			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=-150mA$ $I_B=-15mA$ $I_C=-500mA$ $I_B=-50mA$			-0.4 -1.6	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C=-150mA$ $I_B=-15mA$ $I_C=-500mA$ $I_B=-50mA$			-1.3 -2.6	V
Output capacitance	$C_{ob}$	$V_{CB}=10V$ $f=1.0MHz$			8.0	pF
Input capacitance	$C_{ib}$	$V_{EB}=10V$ $f=1.0MHz$			30	pF
Transition frequency	$f_T$	$V_{CE}=-20V$ $I_C=-50mA$ $f=100MHz$	200			MHz

Turn-on time	$t_{on}$	$V_{CE}=-30V, I_C=-150mA,$ $I_{B1}=-15mA$		45	ns
Delay time	$t_d$			10	ns
Rise time	$t_r$			40	ns
Turn-off time	$t_{off}$	$V_{CE}=-6V, I_C=-150mA$ $I_{B1}=I_{B2}=-15mA$		100	ns
Storage time	$t_s$			80	ns
Fall time	$t_f$			30	ns

**MMBT2907** Typical Characteristics




Figure 1. DC Current Gain




Figure 2. Collector Saturation Region




Figure 3. Capacitances




Figure 4. Current-Gain — Bandwidth Product