



FEATURES

- Normally Open, Single Pole Single Throw
- Control 350 VAC or DC Voltage
- Switch 130 mA Loads
- LED Control Current, 2mA
- Low ON-Resistance
- dv/dt, >500 V/ms
- Isolation Test Voltage, 3750 VAC_{RMS}
- UL, CSA, FCC compatible
- Applications
 - Telecommunications
 - Telecom Switching
 - Tip/Ring Circuits
 - Modem Switching (Laptop, Notebook, Pocket Size)
 - Hookswitch
 - Dial Pulsing
 - Ground Start
 - Ringer Injection
 - Instrumentation
 - Multiplexers
 - Data Acquisition
 - Electronic Switching
 - I/O Subsystems
 - Meters (Watt-Hour, Water, Gas)
 - Medical Equipment
 - High Voltage Test Equipment
 - TRIAC Driver
 - Motor Control
 - Security
 - Aerospace
 - Industrial Controls

DESCRIPTION

The LH1056 is a single pole single throw (SPST), normally open (NO), Mos Relay. The relay can control AC or DC loads currents up to 130 mA, with a supply voltage up to 350 V. The device is packaged in a six pin SMD and dual-in line package. Those package offer an insulation dielectric withstand of 3750 VAC_{RMS}.

The coupler consists of a AlGaAs LED that is optically coupled to a dielectrically isolated photodiode array which drives two series connected high voltage MOS transistors. The typical ON-Resistance is 20Ω at 25 mA and is linear up to 50mA. The incremental resistance drops to less than 20Ω beyond 50 mA while reducing internal power dissipation at high load currents.



Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$)

Emitter (Input)

Reverse Voltage.....	5.0V
Continuous Forward Current.....	50mA
Peak Forward Current (1s).....	1A
Power Dissipation.....	100mW
Derate Linearly from 25°C.....	1.3mW/°C


Detector (Output)

Output Breakdown Voltage.....	±350V
Continous Load Current.....	±130mA
Power Dissipation.....	500mW

General Characteristics

Isolation Test Voltage	3750VAC _{RMS}
Isolation Resistance	$\geq 10^{10}\Omega$
$V_{IO} = 500V, T_A = 25^\circ\text{C}$550mW
Total Power Dissipation	2.5mW/°C
Derate Linearly from 25°C	-40 to + 150°C
Storage Temperature Range	-40 to + 85°C
Operating Temperature Range	-40 to + 85°C
Junction Temperature	100°C
Soldering Temperature, 2mm from case, 10 sec...	260°C

- Turn on/Turn off time




Characteristics

(T_A = 25°C)

Description	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Emitter (Input)						
Forward Voltage	V _F		1.8	2.0	V	I _F = 10 mA
Operation Input Current	I _{IPON}			5	mA	V _L = ± 20 V, I _L = 100 mA, t = 10 ms
Recovery Input Current	I _{IOFF}	0.2			mA	V _L = ± 20 V, I _L = < 5 µA
Detector (output)						
Output Breakdown Voltage	V _B	350			V	I _B = 50 µA
Output Off-State Leakage	I _{T(OFF)}		0.2	1	µA	V _T = 100 V, I _F = 0 mA
I/O Capacitance	C _{ISO}		6		pF	I _F = 0, f = 1 MHz
ON Resistance	Con- nection	A	R _{ON}	20	24	I _L = 100 mA, I _F = 10 mA
		B		10	12	
		C		5	6	
Turn-on Time	T _{ON}		0.3	1.0	ms	I _F = 10 mA, V _L = ± 20 V
Turn-off Time	T _{OFF}		0.7	1.5	ms	t = 10 ms, I _L = ± 100 mA

Mos Relay Schematic and Wiring Diagrams



DATA CURVE

Load current vs. ambient temperature

Allowable ambient temperature:

-40°C to +85°C

On resistance vs. ambient temperature

Across terminals 4 and 6 pin

LED current: 5 mA




Continuous load current: 130 mA(DC)

Turn on time vs. ambient temperature

Load voltage 350 V(DC)

LED current : 5 mA


Continuous load current: 130 mA(DC)




65 Shark River Road, Neptune, New Jersey 07753-7423

Tel: 732-922-6333 Fax: 732-922-6363 E-Mail: globalcomponents.com


Turn off time vs. ambient temperature
LED current: 5mA; Load voltage: 350V(DC)
Continuous load current: 130mA(DC)




LED operate vs. ambient temperature
Load voltage: 350V(DC)
Continuous load current: 130mA(DC)




LED turn off current vs. ambient temperature
Load voltage: 350V(DC)
Continuous load current: 130mA(DC)




LED dropout voltage vs. ambient temperature
LED current: 5 to 50mA




Voltage vs. current characteristics of output at MOS FET portion
Measured portion: across terminals 4 and 6pin
Ambient temperature: 25°C




Off state leakage current
Across terminals 4 and 6pin
Ambient temperature: 25°C



LED forward current vs. turn on time
Across terminals 4 and 6pin; Load voltage: 350V(DC); Continuous load current: 130mA(DC); Ambient temperature: 25°C



LED forward current vs. turn off time
Across terminals 4 and 6pin; Load voltage: 350V(DC); Continuous load current: 130mA(DC); Ambient temperature: 25°C



Applied voltage vs. output capacitance
Across terminals 4 and 6pin
Frequency: 1MHz; Ambient temperature: 25°C

