

# Spec Sheet

High Frequency Multilayer Chip Inductors for Automotive / Industrial Applications (HK series)

## HK160882NJ-TV



### ■ Features

- Item Summary  
82nH(±5%), 180mA, 12, 0603
- Lifecycle Stage  
Mass Production
- AEC-Q200 qualified
- Standard packaging quantity (minimum)  
Taping 4000pcs

### ■ Products characteristics table

CaseSize (EIA/JIS)	0603/1608
Inductance	82nH(±5%)
Inductance Measuring Frequency	100MHz
Rated Current	180mA
DC Resistance (max)	0.95Ω
Avg. of DC.Resistance	0.6Ω
Temperature Range	-40 to +125 °C
Self-resonant Frequency (min)	600MHz
Q (max)	12min
Q Measuring Frequency	100MHz
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow/Wave

### ■ External Dimensions

L	1.6mm ±0.15
W	0.8mm ±0.15
H	0.8mm ±0.15
e	0.3mm ±0.2

2015.04.29

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
Before making final selection, please check product specification.