


Spec Sheet

Multilayer Ceramic Capacitors (High dielectric type) for Automotive / Industrial Applications

UMK325BJ475MNHT



■ Features

- Item Summary
50V, X5R, 4.7 μ F, $\pm$ 20%, 1210
- Lifecycle Stage
Mass Production
- AEC-Q200 qualified
- Standard packaging quantity (minimum)
Taping Embossed 2000pcs

■ Products characteristics table

CaseSize (EIA/JIS)	1210/3225
Rated Voltage (max)	50V
Capacitance	4.7 μ F
Capacitance Tolerance	$\pm$ 20%
Resistance	500 M Ω · μ F min.
Dielectric Loss Tangent	10%MAX
Temperature Characteristics (EIA/JIS)	X5R/-
Temperature Range (EIA/JIS)	-55 to +85°C/-
Capacitance Change (EIA/JIS)	$\pm$ 15/-%
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

■ External Dimensions

L	3.2mm $\pm$ 0.30
W	2.5mm $\pm$ 0.20
T	1.9mm $\pm$ 0.20
e	0.6mm $\pm$ 0.3

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
Before making final selection, please check product specification.

2015.01.28

Multi Layer Ceramic Capacitor

TAIYO YUDEN

-Electrical Characteristics Data-







13R2A05

RoHS compliance product

○UMK325BJ475MNHT

50V 3225 X5R 4.7 μ F $\pm$ 20% $t=2.1$ mmMAX

50V 1210 X5R 4.7 μ F $\pm$ 20% $t=0.083$ inchMAX



部品特性は設置環境、測定条件等により変化する場合があります。本データをご使用される際は実際の製品特性に対する参考データとしてご利用ください。また、本データは予告無く追加・削除及び変更を行う場合があります。ご注文の際は、納入仕様書の確認をお願いします。

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.

TAIYO YUDEN reserves the right to make change to the Date at any time without notice.

Before making final selection, please check product specification