

12.6kW 3-Phase Monitored PDU, 208V Outlets (30-C13 & 6-C19), IEC-309 60A Blue, 10ft Cord, 0U Vertical

MODEL NUMBER: PDU3VN10G60



Description

Tripp Lite 3 phase Monitored PDU / Power Distribution Unit offers real-time remote monitoring of voltage, frequency and load levels via built-in network connection. PowerAlert interface supports custom notification of user-specified remote conditions via email, secure web, SNMP, Telnet or SSH interface. PDU output current consumption in amps is displayed per-phase via front panel lighted digital display and can be monitored remotely to warn of potential overloads before critical IT mains breakers trip.

Features

- 12.6kW 3 phase 208V Monitored Power Distribution Unit / PDU with built-in web/network interface
- Attached IEC-309 Blue 60A (3P+E) 208V 3 phase input plug with 10 ft. / 3m cord
- 0U, 70 in. / 178cm vertical form factor supports installation in 2 or 4 post equipment racks
- 36 total 208V outlets (30 C13, 6 C19) arranged in three breakered single phase output load banks
- Lighted display with scroll-button reports power consumption in amps for all 3 loading banks, IP-address self-identification and 180 degree display rotation for overhead or raised floor power feeds
- Built-in SNMP/ethernet interface reports voltage, frequency and PDU loading per-phase via network or secure web browser interface with options for user specified alarm and notification thresholds
- Supports in-rack environmental reporting with optional ENVIROSENSE temperature / humidity sensor and rack access notification with up to 4 optional SRSWITCH door sensors
- DHCP/Manual configuration support
- 10/100 Mbps auto-sensing allows optimal communication with 10/100 Base-T networks
- Real-time clock backup maintains the time of day and date even if the PDU is unpowered
- Tiered access privileges allow an administrator and a guest to login via web browser for monitoring
- Alert notifications via email or SNMP traps offer immediate event notification
- Firmware upgrade ability supports future product enhancements
- Supports HTTP, HTTPS, PowerAlert Network Management System, SMTP, SNMPv1, SNMPv2, SNMPv3, Telnet, SSH, FTP, DHCP, BOOTP, NTP

Highlights

- Monitored 12.6kW 3 Phase 208V PDU; 70 in. / 178cm 0U vertical rackmount
- Reports voltage, frequency and load per-phase via built in ethernet interface
- Visual current meter; Toolless button-mount installation
- IEC-309 Blue 60A (3P+E) 208V 3 phase input; 10 ft. / 3m line cord
- 30 C13 & 6 C19 single phase outlets; Included cord retention brackets
- Temperature, humidity and contact closure monitoring options

Applications

Ideal for 3 phase network configurations in datacenters and heavily configured equipment racks

Package Includes

- Monitored rackmount PDU with pre-installed mounting buttons
- Cord retention brackets
- Spare installation buttons (2 9mm / 4 6mm)
- Rack mounting brackets
- Owner's manual

protocols

- Fully compatible with FREE PowerAlert Network Management System / NMS Software
- Included cord retention brackets keep vital network equipment plugged in and continuously powered
- Toolless mounting supported in button-mount compatible racks, plus nut-and-bolt mounting brackets for other mounting applications (set of 2 9mm buttons pre-installed, 2 9mm and 4 6mm spare buttons included)
- TAA Compliant Version Available - Order Tripp Lite PDU3VN10G60WTAA

Specifications

| OVERVIEW | |
|-----------------------------------|--|
| Style | Vertical rackmount |
| PDU Type | Monitored |
| OUTPUT | |
| Output Capacity Details | 12.6kW total capacity; 20A max per phase; 16A max per C19 outlet; 12A max per C13 outlet |
| Frequency Compatibility | 60 Hz |
| Output Receptacles | (30) C13; (6) C19 |
| Output Nominal Voltage | 208V single phase |
| Overload Protection | 3 20A double-pole circuit breakers (1 per output phase) |
| Outlet Type | IEC-C13, IEC-C19 |
| INPUT | |
| PDU Input Voltage | 208 |
| Maximum Input Amps | 35 |
| PDU Plug Type | IEC-309 60A BLUE (3P+E) |
| Input Cord Length (ft.) | 10 |
| Input Cord Length (m) | 3.05 |
| Input Phase | 3-Phase |
| USER INTERFACE, ALERTS & CONTROLS | |
| Front Panel LEDs | 2 digit current meter display reports output amps per phase and IP address |
| Switches | Pushbutton switches enable local display of each phase separately, display rotate and display IP address functions |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 6.6 x 9.3 x 75.5 |
| Shipping Dimensions (hwd / cm) | 16.8 x 23.6 x 191.8 |
| Shipping Weight (lbs.) | 24.3 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|--|
| Shipping Weight (kg) | 11 |
| Unit Dimensions (hwd / in.) | 70 x 2.19 x 1.76 |
| Unit Dimensions (hwd / cm) | 177.8 x 5.6 x 4.47 |
| Unit Weight (lbs.) | 17.1 |
| Unit Weight (kg) | 7.8 |
| Material of Construction | Steel |
| Form Factors Supported | Vertical rackmount installation supported with included mounting brackets; supports toolless mounting in button-mount compatible racks |
| PDU Form Factor | Vertical (0U) |
| ENVIRONMENTAL | |
| Relative Humidity | 0-95% non-condensing |
| CERTIFICATIONS | |
| TAA Compliant Option | TAA Compliant Version Available - Order Tripp Lite PDU3VN10G60WTAA |
| Certifications | Tested to UL60950-1 (USA, Canada), NOM (Mexico), Class A (Emissions), ROHS |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.