

## Complete Buffered 16-Bit DAC

### FEATURES

- True 16-bit (0.0008%) linearity
- $\mu$ P compatible
- Complete
- 24-pin package
- Low power — 450mW
- Low cost
- Binary or BCD code


### DESCRIPTION

The DAC9377-16 is a complete, voltage output 16-bit D/A converter with true 16-bit linearity. Complete with storage registers, internal reference and output amplifier, the DAC9377-16 provides the user with exceptional performance and self-contained operation. The input storage register is composed of 16 parallel latches — a system compatible with 16-bit data bus interfaces. A single proprietary monolithic chip contains switches, storage registers and other electronics for high resolution and low linearity error. TTL and CMOS compatibility combined with low power dissipation in a ceramic 24-pin DIP makes the DAC9377-16 unsurpassed in a high resolution data conversion device.

**True 16-Bit Linearity** — 16-bit ( $\pm 0.0008\%$ ) linearity in a 24-pin DIP is unequalled. No other microcircuit converter does better. Additional versions with 15- and 14-bit linearity are also available.

**Low Power** — CMOS proprietary monolithic devices in a unique circuit configuration yield the lowest power dissipation (450 mW typ.) of any complete 16-bit converter available.

**Complete** — No external components are required for 16-bit conversion.




**Input Storage Registers** — Designed in one 16-bit segment, the input storage register provides data storage when latched, but is “transparent” when unlatched. The latch control is level triggered for either static or dynamic operation.

**Reliability** — A proven performer, the DAC9377-16 is packaged in a 24-pin ceramic DIP for the utmost in reliability. Combined with our proprietary monolithic device and automatic wirebonding, we’ve made the DAC9377-16 the most reliable device to date. Reliability is further enhanced by batch-processed, precision laser-trimmed resistor networks fabricated in our own facility.

Advanced designs, proven processes and continuous monitoring during all production operations by our quality control organization are combined with rigorous AQL screening to provide the most dependable, low cost D/A converter possible.

### FUNCTIONAL DIAGRAM



# DAC9377

## SPECIFICATIONS

(Typical @+25°C unipolar operation and nominal power supply, no load)

MODEL	DAC9377-16-6	DAC9377-16-5	DAC9377-16-4	DAC9377-4D
TYPE	Latched Inputs			
<b>DIGITAL INPUT</b>				
Resolution	16-Bits			
Unipolar Coding	Binary			BCD
Bipolar Coding	Offset Binary			N.A.
Logic Compatibility <sup>1</sup>	TTL, CMOS			
Input Leakage Current	$\pm 1\mu\text{A}$ (max): $0.4\text{V} > V_{\text{LOGIC}} > 3.2\text{V}$			
Latch Control Width	250nS (min)			
Data Set-up Time <sup>2</sup>	500nS (min)			
Data Hold Time <sup>3</sup>	OnS (min)			
<b>ANALOG OUTPUT</b>				
Scale Factor <sup>4</sup>	0.1% F.S.R. (typ)			
Initial Offset <sup>4</sup>	0.15% P.S.R. (max)			
Unipolar	$\pm 0.05\%$ F.S.R. (max)			N.A.
Bipolar	$\pm 0.10\%$ F.S.R. (max)			
Voltage Range				
Unipolar	0 to +10V			N.A.
Bipolar	$\pm 10\text{V}$			
Current Compliance	$\pm 5\text{mA}$			
Output Impedance	<0.1			
Noise				
PP-noise (wideband)	$\pm 0.0005\%$ F.S.R.			
<b>REFERENCE</b>				
Voltage	-10V (internal)			
Drift	5ppm/°C			
Stability	1mV/yr			
<b>STATIC PERFORMANCE</b>				
Integral Linearity <sup>6</sup>	$\pm 0.0008\%$ F.S.R. (typ)	$\pm 0.0015\%$ F.S.R. (typ)	$\pm 0.0015\%$ F.S.R. (typ)	$\pm 0.002\%$ F.S.R. (typ)
	$\pm 0.0015\%$ F.S.R. (max)	$\pm 0.002\%$ F.S.R. (max)	$\pm 0.003\%$ F.S.R. (max)	$\pm 0.005\%$ F.S.R. (max)
Differential Linearity <sup>7</sup>	$\pm 0.0004\%$ F.S.R. (typ)	$\pm 0.0008\%$ F.S.R. (typ)	$\pm 0.0015\%$ F.S.R. (typ)	$\pm 0.005\%$ F.S.R. (typ)
	$\pm 0.0015\%$ F.S.R. (max)	$\pm 0.003\%$ F.S.R. (max)	$\pm 0.006\%$ F.S.R. (max)	$\pm 0.01\%$ F.S.R. (max)
Monotonicity	Guaranteed to 16-bits	Guaranteed to 15-bits	Guaranteed to 14-bits	
<b>DYNAMIC PERFORMANCE</b>				
Major Carry Transition Settling to 0.006% F.S.R. (strobed)	20 $\mu\text{S}$			
Slew Rate	0.20V/ $\mu\text{S}$			
<b>STABILITY<sup>5</sup></b>				
(Over Specified Temp. Range)				
Gain	8ppm/°C F.S.R. (max)			5ppm/°C
Linearity	1ppm/°C F.S.R. (max)			
Differential Linearity	1ppm/°C F.S.R. (max)			5ppm/°C
Offset Drift				
Unipolar	3ppm/°C F.S.R.			
Bipolar	5ppm/°C F.S.R.			
<b>POWER SUPPLY</b>				
Requirements	+15V $\pm 5\%$ @ 15mA (max) -15V $\pm 5\%$ @ 20mA (max)			
Rejection Ratio	0.003% /% (max)			
Power Dissipation	450mW, 600mW max			

(Continued on next page.)

# DAC9377

## TEMPERATURE RANGE

Operating	0°C to +70°C
Storage	-25°C to +85°C


## MECHANICAL

Case Style	24 pin. double-DIP
Case Dimensions	

### NOTES:

\* Same as DAC9377-16-6

- Digital input voltage must not exceed supply voltage or go below -0.5V;
- Time, data must be stable before latch control goes to "0".
- Time, data must be stable after latch control goes to "0".
- See APPLICATIONS INFORMATION for calibration procedure.
- See APPLICATIONS NOTES.
- Integral Linearity, for this product, is measured as the arithmetic mean value of the magnitudes of the greatest positive deviation and the greatest negative deviation from the theoretical value for any given input combination.
- Differential Linearity is the deviation of an output step from the theoretical value of 1 LSB for any two adjacent digital input codes.



### Pin Connections

Unipolar Output: Ground pin 11 (No Connection for BCD)

Bipolar Output: Connect pin 11 to pin 9 (Binary Only)

### PIN DESIGNATIONS

PIN	FUNCTION		PIN	FUNCTION	
	Binary	BCD		Binary	BCD
1	2 <sup>-8</sup>	(100)	24	2 <sup>-9</sup>	(80)
2	2 <sup>-7</sup>	(200)	23	2 <sup>-10</sup>	(40)
3	2 <sup>-6</sup>	(400)	22	2 <sup>-11</sup>	(20)
4	2 <sup>-5</sup>	(800)	21	2 <sup>-12</sup>	(10)
5	2 <sup>-4</sup>	(1000)	20	2 <sup>-13</sup>	(8)
6	2 <sup>-3</sup>	(2000)	19	2 <sup>-14</sup>	(4)
7	2 <sup>-2</sup>	(4000)	18	2 <sup>-15</sup>	(2)
8	2 <sup>-1</sup>	(8000)	17	2 <sup>-16</sup>	(1)
9	SUMMING JUNCTION		16	LATCH CONTROL	
10	OUT		15	-15V	
11	BIPOLAR	N/C	14	GAIN ADJUST	
12	+15V		13	GND	

Note on BCD pin 11 must have no connection

Consult factory for application information.

## ORDERING INFORMATION

MODEL	DESCRIPTION
DAC9377-16-6	16-Bit DAC with 16-bit linearity
DAC9377-16-5	16-Bit DAC with 15-bit linearity
DAC9377-16-4	16-Bit DAC with 14-bit linearity
DAC9377-4D	16-Bit 4 Decade BCD

Specifications subject to change without notice.