****TELEDYNE MEC**

11361 Sunrise Park Drive, Rancho Cordova, Calif. 95742-6587 Telephone (916) 638-3344 Fax (916) 636-7453

This model number is controlled by the International Traffic in Arms Regulations, and can only be exported via a U.S. Department of State export license. They may not be transferred, transshipped on a non-continuous voyage, or otherwise be disposed of in any other country, either in their original form or after being incorporated into other end-items, without the prior written approval of the U.S. Department of State.

MODEL NO. MEC 5409 (GR) MEC 5410 (FE)

6.5 to 18.0 GHz

TYPI	CAL ()PEF	rating con	POWER SUPPLY REQUIREMENTS			
ELEMENT		VOLTAGE	CURRENT	VOLTAGE MIN	VOLTAGE MAX	CURRENT MAX	
HEATER		-6.3 Vdc	1.6 A	-6.0 Vdc	-6.6 Vdc	2 A	
HELIX			GROUND	7 mA	GROUND		15 mA
FE ON		-50 Vdc	1 mA 0.1 mA	0	-75 Vdc	1 mA	
FE OFF		-1300 Vdc	0.1 mA	-1500 Vdc	-1700 Vdc	1 mA	
GRID ON		180 Vdc	1 mA	125 Vdc	250 Vdc	10 mA	
GRID OFF		-200 Vdc	0.1 mA	-200 Vdc	-500 Vdc	1 mA	
CATHODE (Ek)		-10.3 kV	260 mA	-10 kV	-10.5 kV	280 mA	
COLLEC	TOR	#1	5.36 kV	45 mA	52% × El	< ± 2%	100 mA
W/ RI	F	#2	3.71 kV	208 mA	36% x Ek ± 2%		280 mA

NOTE 1: CATHODE VOLTAGE IS MEASURED WITH RESPECT TO GROUND.

NOTE 2: HEATER, COLLECTOR, GRID OR FOCUS ELECTRODE (FE) VOLTAGES ARE MEASURED WITH RESPECT TO CATHODE.

SELECTED PERFORMANCE	TYPICAL	SPECIFIED	
INPUT VSWR	2:1	2.5:1	
OUTPUT VSWR	2:1	2.25:1	
MAXIMUM DUTY		CW	
FE CAPACITANCE	50 pF	65 pF	
GRID CAPACITANCE	37 pF	50 pF	
MIN HARMONIC SEPARATION	-6 dBc	-5 dBc *	
NOISE POWER DENSITY	-15 dBm/MHz	-10 dBm/MHz	
PRIME POWER	1095 W	1400 W	
TEMPERATURE RANGE	-40° to 85°C		

RF PERFORMANCE							
FREQ GHz	TYP SAT POWER OUTPUT (WATTS)	MIN SPEC POWER OUTPUT (WATTS)	TYP GAIN AT SPEC POWER dB				
6.5	215	200 *	35				
7.0	240	200	40				
8.0	250	200	41				
9.0	275	200	43				
10.0	225	200	45				
11.0	275	200	45				
12.0	275	200	46				
13.0	275	200	46				
14.0	275	200	45				
15.0	250	200	43				
16.0	240	200	41				
17.0	230	200	48				
18.0	220	200	35				

TYPICAL POWER OUTPUT IS SHOWN TO ILLUSTRATE CAPABILITY.

GAIN IS WITH EQUALIZER.

An ISO 9001:2000 Quality System Certified Company

01/06