

## FEATURES

- True double-conversion online UPS
- Output power factor 0.9
- User-friendly and easy-shift LCD display
- Rack/Tower design
- Programmable power management outlets
- 50/60Hz frequency converter mode
- ECO and advanced ECO mode for energy saving
- Emergency power off function (EPO)
- Hot-swappable battery design for 1-3K models only
- DSP technology applied for 6K and up models
- Active input power factor correction 0.99 for 6K and up models
- N+X paralalled redundancy available for 6K and up models



## PHASE (ONLY FOR ONLINE UPS)

**Phase:** 1-phase in / 1-phase out

## INPUT

**Capacity:** 1000 VA / 900 W  
**Voltage:** 100\*/110\*/115\*/120 VAC or 208/220/230/240 VAC  
**Voltage Range:** 55-150 VAC ± 5% or 110-300 VAC ± 5%  
**Frequency Range:** 40Hz ~ 70 Hz

## OUTPUT

**AC Voltage Regulation (Batt. Mode) :** ± 1%  
**Frequency Range (Batt. Mode):** 47~ 53 Hz or 57 ~ 63 Hz  
**Waveform (Batt. Mode):** Pure Slin Wave

## BATTERY

**Battery Type:** 12 V/9 Ah  
**Battery Number:** 2  
**Typical Recharge Time:** NONE

## SAFETY STANDARD APPAOVAL



## PROTECTION

**Full Protection:** Full Protection

## PHYSICAL

**Output Receptacles:** India, French, Schuko, NEMA, and IEC selections  
**Dimension:** 380mm(L) x 438mm(W) x 88mm(H)  
**Net Weight (kgs):** 12.9

## OPERATING ENVIRONMENT

**Humidity:** 20-90% RH @ 0-40°C (non-condensing)  
**Noise Level:** Less than 50dB @ 1 Meter

## MANAGEMENT

**Optional USB/RS-232 Port:** Support Windows 98/2000/2003/XP/Vista/2008, Windows 7, Linux, and MAC

This content is subject to change, please refer to specification for more detail. FSP reserve the right to change the content without prior notice