



ISOMETRIC

SWITCH FUNCTION	
POS. 1	POS. 2
ON	(ON)
1-3	1-2

(ON) = MOMENTARY



PCB LAYOUT

- NOTE:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERMINAL NUMBERS FOR REF ONLY
 - ▲ 4. PLATING MATERIAL: SILVER
 5. RATING: 3A @ 120VAC OR 28VDC
1A @ 250VAC
 6. CONTACT RESISTANCE: 20 mOHMS
100 mA
 7. LIFE EXPECTANCY: 50,000 MAKE-AND-BREAK CYCLES
Min. AT FULL LOAD.
 8. INSULATION RESISTANCE: 1,000 MEGA-OHM MIN.
 9. DIELECTRIC STRENGTH: 1,500 V RMS @SEA LEVEL.
 10. OPERATING TEMP.: -30°C to 75°C
 11. 2002/95/EC (ROHS) COMPLIANT
 12. ▲ DENOTES CRITICAL PARAMETER.



A	18005	RELEASED FOR PRODUCTION	3/14/08	BLR
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE 700ASP7B10M7QE				
SCALE	DATE	DR	DWG	REV
2:1	3/14/2008	BLR	T750104	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED