

# AMI401-945

Expandable Type for IBASE MI945F  
Mini-ITX Motherboard

Fanless System

# AMI402-910

Expandable Type for IBASE MI910EF  
Mini-ITX Motherboard

Fanless System



01  
Motherboards

02  
Disk-Size SBCs

03  
CPU Modules

04  
PC 104 Plus

05  
CPU Cards

06  
RISC SBCs

07  
Embedded Systems



## Features

- Fanless system with IBASE MI945F Mini-ITX motherboard
- One expansion slot outlet on rear panel
- Available in silver (aluminum) color
- One 2.5" HDD drive bay
- Rear panel: exchangeable I/O shield
- 2x USB, power button ( LED ) / Reset button (HDD LED) in front for easy connection
- Wall mount kit included

## Specifications

System Mainboard	MI945F
CPU Type	Intel® Core™2 Duo T9400
System Speed	2.53GHz
Memory	2x DDR2 SO-DIMM, 4GB
Construction	Aluminum & Steel
Chassis Color	Silver (Aluminum)
Front Panel External I/O	Power LED, HDD LED, Power button, Reset button, 2x USB ports
Rear Panel External I/O	Audio, 2x LAN, 4x USB, COM, VGA, SPDIF, 1394, KB/MS
Storage	1x 2.5" HDD drive bay
Power Supply	150W power adaptor
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	226mm(W) x 263.5mm(D) x 109mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating: 1.0 grms / 5~500Hz / random Operating: 0.25 grms / 5~500Hz / random

## Ordering Information

AMI401-945FC-D1	Aluminum Chassis for MI945F, 2.5" HDD holder, ID450 converter, 150W Power
AMI401-945F-D1	Aluminum System with MI945F, Intel® T9400 (2.53GHz) CPU, 4GB DDR2 SO-DIMM, 2.5" 320GB HDD, ID450 converter, 150W Power

## Features

- Fanless system with two expansion slots available on rear panel
- One 2.5" HDD drive bay
- Optional DC-in, 2nd COM (RS232/422/485) and DVI reserved for custom design
- 2x USB, Power/Reset button, Power/HDD status LED
- Wall mount kit included
- Available in silver (aluminum) color

## Specifications

System Mainboard	MI910EF
CPU Type	Intel® Core™2 Duo T7500
System Speed	2.2GHz
Memory	2x DDR2 DIMM, Max. 2GB
Construction	Aluminum & Steel
Chassis Color	Silver (Aluminum)
Front Panel External I/O	Power LED, HDD LED, Power button, Reset button, 2x USB ports
Rear Panel External I/O	1x VGA, 1x DVI, 1x COM, 4x USB ports, 2x RJ45 connectors, 1x 1394, audio, SPDIF, KB/MS connector, DC-in jack
Storage	1x 2.5" HDD drive bay
Power Supply	150W power adaptor
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	226mm(W) x 263.5mm(D) x 109mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating: 1.0 grms / 5~500Hz / random Operating: 0.25 grms / 5~500Hz / random

## Ordering Information

AMI402-910EFC-D1	Aluminum System for MI910EF, Fanless Design for CPUs Max. 35W, w/ ID450 (DC-DC converter), 150W power adaptor, 2.5" HDD holder
AMI402-910EFM-D1	Aluminum System with MI910EF, Fanless Design for CPUs Max. 35W, w/ ID450 (DC-DC converter), 150W power adaptor, 2.5" HDD holder, IP340 (2 PCI riser card), ID391-R (DVI board)
AMI402-910EF-D1	Aluminum System with MI910EF, Fanless Design w/ Intel® T7500 (2.2GHz) CPU, 2GB DDR2 DIMM, 2.5" 320GB HDD, w/ ID450 (DC-DC converter), 150W power adaptor, IP340 (2 PCI riser card), ID391-R (DVI board)

Remarks: 1. Specifications are subject to change without prior notice.  
2. ODM/OEM is available